

Tel: 800-752-9326 **Fax:** 763-389-2725

SRWProducts.com

PO Box 70 32005 126th St Princeton, MN 55371

SRW Silver Elite

SRW Products Manufactures/Supplies a 100% Polypropylene Non-Woven Thermal Bonded Filament Fibers marketed as **SRW Silver Elite**. With excellent dimensional stability and low shrinkage, our Spun Bond products serve as the professional's choice for landscape and geotextile projects. The fabric will not rot or mildew, is non-biodegradable with superior UV resistance, and is resistant to damage from insects and rodents.

SRW Silver Elite meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Grab Tensile	ASTM D 4632	lbs.	112
Thickness	ASTM D 5199	mm	0.6
Grab Elongation	ASTM D 4632	lbs.	60
Trap Tear	ASTM D 4533	lbs.	56
Puncture	ASTM D 6241	lbs.	236
Permittivity	ASTM D 4491	sec ⁻¹	2.60
Water Flow	ASTM D 4491	gpm/ft²	133
UV Resistance	ASTM D 4355	% @ 500 Hrs.	70
AOS	ASTM D 4751	US Sieve	50

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.