



Tel: 800-752-9326  
 Fax: 763-389-2725  
 SRWProducts.com

PO Box 70  
 32005 126th St  
 Princeton, MN 55371

# 100% Coconut Fiber Blanket

## Double Sided Net

SRW Coconut Blankets are made with uniformly distributed 100% coconut fiber and two polypropylene nets securely sewn together with UV stabilized thread. The tightly compressed blankets are wrapped and include a product label, code and installation guide. The blankets are palletized for easy transportation. The ECC-2™ has functional longevity of approximately 36 months, but will vary depending on soil and climatic conditions, and is suitable for slopes 1:1 and medium to high flow channels. SRW 100% Coconut Blanket meets Type 4 specification requirements established by the Erosion Control Technology Council (ECTC) and Federal Highway Administration's (FHWA) FP-03 Section 713.17.

SRW 100% Coconut Fiber Blankets meet or exceed the physical property values listed below.

Physical Property	Test Method	Minimum Average Roll Value		
Matrix		100% Coconut Fibers		
Netting Material		Polypropylene (Double Sided)		
Netting Type		Extended-Term Photodegradable		
Mass/Unit Area	ASTM D 6475	8.30 oz/yd <sup>2</sup>		
Thickness	ASTM D 6525	0.26 in		
Blanket Life (Avg)		24-36 months		
Slope Rating	ASTM D 6459	1:1 or greater		
Tensile Strength (MD)	ASTM D 6818	260 lb/ft		
Elongation (MD)	ASTM D 6818	20%		
Light Penetration	ASTM D 6567	16% Open		
Water Absorption	ASTM D 1117	199%		
Net Opening Dimensions		0.75 in x 0.75 in (Top Net) 0.75 in x 0.75 in (Bottom Net)		
Roll Sizes	Sq Yds / Roll	Size	Roll Weight	Qty Per Pallet
FCMB C081125	100.00	8' x 112.5'	57 lbs	25

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.