



Tel: 800-752-9326  
Fax: 763-389-2725  
SRWProducts.com

PO Box 70  
32005 126th St  
Princeton, MN 55371

## SRW 370HP

SRW Products Manufactures/Supplies a 100% Polypropylene, monofilament yarn called SRW 370HP offering optimum performance when used in stabilization applications. Produced from first quality raw material, they provide the perfect balance of strength and separation. The fabric will not rot or mildew, is non-biodegradable, and is resistant to damage from insects and rodents.

SRW 370HP meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Wide Width Tensile	ASTM D 4595	lbs./ft	3600x3300 (52.5 x 48.2 kN)
Wide Width Tensile (2% Strain)	ASTM D 4595	lbs./ft	540x540 (7.9 x 7.9 kN)
Wide Width Tensile (5% Strain)	ASTM D 4595	lbs./ft	1500x1560 (21.9 x 22.8 kN)
Wide Width Tensile (10% Strain)	ASTM D 4595	lbs./ft	2400 x 2400 (35 x 35 kN)
Permeability	ASTM D 4491	cm/sec	.05
Permittivity	ASTM D 4491	sec <sup>-1</sup>	.52
AOS	ASTM D 4751	US Sieve	30 (.60 mm)
Water Flow	ASTM D 4491	gpm/ft <sup>2</sup>	40 (1630 lpm/m <sup>2</sup> )
UV Resistance	ASTM D 4355	% Strength Retained @500 hours	80

### Roll size 15' x 300'

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.