



Tel: 800-752-9326
Fax: 763-389-2725
SRWProducts.com

PO Box 70
32005 126th St
Princeton, MN 55371

SRW MM402

SRW Products Manufactures/Supplies a 100% Polypropylene, monofilament yarn called SRW MM402 offering optimum performance when used in stabilization applications. Produced from first quality raw material, they provide the perfect balance of strength and separation. The fabric will not rot or mildew, is non-biodegradable, and is resistant to damage from insects and rodents.

SRW MM402 meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Grab Tensile Strength	ASTM D 4632	lbs./ft	365 x 200
Wide Width Tensile	ASTM D4595	lbs./ft	2400 x 1680
Grab Elongation	ASTM D 4632	%	24 x 15
Trapezoidal Tear	ASTM D 4533	lbs./ft	115x75
CBR Puncture	ASTM D 6241	lbs./ft	750
Permittivity	ASTM D 4491	sec ⁻¹	2.1
Permeability	ASTM D 4491	cm/sec	.14
AOS	ASTM D 4751	US Sieve	40
Water Flow	ASTM D 4491	gpm/ft ²	145
Percent Open Area	COE-02215	%	10%
UV Resistance	ASTM D 4355	% Strength Retained @500 hours	90
Roll Size		L x W ft (sy)	12 x 300 (400)

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.