



**Tel:** 800-752-9326  
**Fax:** 763-389-2725  
**SRWProducts.com**

PO Box 70  
32005 126th St  
Princeton, MN 55371

## SRW PP350

SRW Products Manufactures/Supplies a 100% Polypropylene, monofilament yarn called SRW PP350 offering optimum performance when used in stabilization applications. Produced from first quality raw material, they provide the perfect balance of strength and separation. The fabric will not rot or mildew, is non-biodegradable, and is resistant to damage from insects and rodents.

SRW PP350 meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Grab Tensile Strength	ASTM D 4632	lbs./ft	350 x 200
Grab Elongation	ASTM D 4632	%	15 x 15
Trapezoidal Tear	ASTM D 4533	lbs./ft	100 x 70
CBR Puncture	ASTM D 6241	lbs./ft	800
Percent Open Area	CEO-02215	%	6
Permittivity	ASTM D 4491	sec <sup>-1</sup>	.5
Permeability	ASTM D 4491	cm/sec	.14
AOS	ASTM D 4751	US Sieve	40
Water Flow	ASTM D 4491	gpm/ft <sup>2</sup>	60
UV Resistance	ASTM D 4355	% Strength Retained @500 hours	90
Roll Size		L x W ft (sy)	12x300 6x300

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.