

Safety Data Sheet

SRW Retaining Wall Adhesive

Section 1. Identification

GHS product identifier : SRW Retaining Wall Adhesive:
Product type Liquid.
Address : SRW Products
32005 126th Street, PO Box 70
Princeton, MN 55371
Contact person : SRW Products Technical Services
Telephone : (800) 752-9326
In case of emergency : Chemtrec
(800) 424-9300
Product code : 56491
Date of revision : 04-27-2020.
Print date : 04-27-2020.
Chemtrec (24 Hour) : (800) 424 - 9300
Chemtrec International : (703) 527 - 3887
Relevant identified uses of the substance or mixture and uses advised against
Not applicable.

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
GHS label elements CARCINOGENICITY (inhalation) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (eyes) (oral) - Category 1
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation and Narcotic effects) - Category 3



Hazard pictograms :
Signal word : Danger
Hazard statements : Highly flammable liquid and vapor.
Precautionary statements : Causes serious eye irritation.
Suspected of causing cancer if inhaled.
Causes damage to organs if swallowed.
(eyes) May cause respiratory irritation.
May cause drowsiness and dizziness.

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only nonsparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated

area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

- Response** : IF exposed: Call a POISON CENTER or physician. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
- Storage** : Store locked up. Store in a well-ventilated place. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Avoid contact with skin and clothing. Wash thoroughly after handling.
- Hazards not otherwise classified** : Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Hazardous ingredients United States

Name	CAS number	%
methyl acetate	79-20-9	25 - 50
methanol	67-56-1	0.1 - 0.5
vinyl acetate	108-05-4	0.1 - 0.5
6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol	119-47-1	0 - 0.1

Canada

Name	CAS number	%
methyl acetate	79-20-9	25 - 50
oxydipropyl dibenzoate	27138-31-4	1 - 5
methanol	67-56-1	0.1 - 0.5
vinyl acetate	108-05-4	0.1 - 0.5

Mexico

Name	CAS number	UN number	%	IDLH	Classification			
					H	F	R	Special
methyl acetate	79-20-9	UN1993	25 - 50	3100 ppm	2	3	0	-
oxydipropyl dibenzoate	27138-31-4	Not available.	1 - 5	-	2	0	0	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Causes damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following: respiratory tract irritation coughing
nausea or vomiting headache
drowsiness/fatigue dizziness/vertigo
unconsciousness
Adverse symptoms may include the following:
irritation
dryness
- Skin contact** : cracking
No specific data.
- Ingestion** :

Section 4. First aid measures

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** :
- Unsuitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Specific hazards arising from the chemical** : Do not use water jet.
- Hazardous thermal decomposition products** : Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
- Special protective actions for fire-fighters** : Decomposition products may include the following materials: carbon dioxide carbon monoxide
- Special protective equipment for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions, protect personnel** : **Personal precautions, protect personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods and materials for containment and cleaning up** : **Methods and materials for containment and cleaning up** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling :

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges.

: Empty containers retain product residue and can be hazardous. Do not reuse container. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Advice on general occupational hygiene

Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: -17 to 40°C (1.4 to 104°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

United States

Occupational exposure limits

Ingredient name	Exposure limits
<p>methyl acetate</p> <p>SRW Retaining Wall SP Adhesive</p>	<p>ACGIH TLV (United States, 4/2014). TWA: 200 ppm 8 hours. TWA: 606 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 757 mg/m³ 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 200 ppm 8 hours. TWA: 610 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 760 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2013). TWA: 200 ppm 10 hours. TWA: 610 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 760 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours.</p>

Section 8. Exposure controls/personal protection

methanol	<p>TWA: 610 mg/m³ 8 hours.</p> <p>ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 200 ppm 8 hours. TWA: 262 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 328 mg/m³ 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2013). Absorbed through skin. TWA: 200 ppm 10 hours. TWA: 260 mg/m³ 10 hours. STEL: 250 ppm 15 minutes. STEL: 325 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 2/2013). TWA: 200 ppm 8 hours. TWA: 260 mg/m³ 8 hours.</p>
vinyl acetate	<p>ACGIH TLV (United States, 4/2014). TWA: 10 ppm 8 hours. TWA: 35 mg/m³ 8 hours. STEL: 15 ppm 15 minutes. STEL: 53 mg/m³ 15 minutes.</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 10 ppm 8 hours. TWA: 30 mg/m³ 8 hours. STEL: 20 ppm 15 minutes. STEL: 60 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2013). CEIL: 4 ppm 15 minutes. CEIL: 15 mg/m³ 15 minutes.</p>

Canada

Occupational exposure limits		TWA (8 hours)			STEL (15 mins)			Ceiling			
Ingredient	List name	ppm	mg/m ³	Other	ppm	mg/m ³	Other	ppm	mg/m ³	Other	Notations
methyl acetate	US ACGIH 4/2014	200	606	-	250	757	-	-	-	-	
	AB 4/2009	200	606	-	250	757	-	-	-	-	
	BC 4/2014	200	-	-	250	-	-	-	-	-	
	ON 1/2013	200	606	-	250	757	-	-	-	-	
methanol	QC 1/2014	200	606	-	250	757	-	-	-	-	
	US ACGIH 4/2014	200	262	-	250	328	-	-	-	-	[1]
	AB 4/2009	200	262	-	250	328	-	-	-	-	[1]
	BC 4/2014	200	-	-	250	-	-	-	-	-	[1]
vinyl acetate	ON 1/2013	200	262	-	250	328	-	-	-	-	[1]
	QC 1/2014	200	262	-	250	328	-	-	-	-	[1]
	US ACGIH 4/2014	10	35	-	15	53	-	-	-	-	
	AB 4/2009	10	35	-	15	53	-	-	-	-	
	BC 4/2014	10	-	-	15	-	-	-	-	-	
	ON 1/2013	10	35	-	15	53	-	-	-	-	
	QC 1/2014	10	35	-	15	53	-	-	-	-	

[1] Absorbed through skin.

Mexico

Occupational exposure limits

Ingredient	Exposure limits
methyl acetate	NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 200 ppm 8 hours. LMPE-PPT: 610 mg/m ³ 8 hours. LMPE-CT: 760 mg/m ³ 15 minutes. LMPE-CT: 250 ppm 15 minutes.

Consult local authorities for acceptable exposure limits.

Section 8. Exposure controls/personal protection

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state	
Color	: Liquid. [Paste.] :
Odor	Beige.
Odor threshold	: Solvent(s) [Strong] :
pH	Not available.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: 54.44°C (130°F)
Evaporation rate	: Closed cup: -13°C (8.6°F) [Setaflash.]
Flammability (solid, gas)	: >1 (butyl acetate = 1) : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

Section 9. Physical and chemical properties

VOC (less water, less : 7 g/l exempt solvents)

Relative density : 1.306

Solubility : Insoluble in the following materials: cold water and hot water.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
methyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
methanol	LC50 Inhalation Gas.	Rat	145000 ppm	1 hours
	LC50 Inhalation Gas.	Rat	64000 ppm	4 hours
vinyl acetate	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-
	LC50 Inhalation Vapor	Rat	11400 mg/m ³	4 hours
	LD50 Dermal	Rabbit	2335 mg/kg	-
6,6'-di-tert-butyl-2,2'methylenedi-p-cresol	LD50 Oral	Rat	2900 mg/kg	-
	LD50 Oral	Rat	4880 mg/kg	-

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
methyl acetate	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
Skin - Mild irritant	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
Skin - Moderate irritant	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
methanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant Skin - Moderate irritant	Rabbit Rabbit	- -	40 milligrams 24 hours 20 milligrams	- -
6,6'-di-tert-butyl-2,2'methylenedi-p-cresol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-

Conclusion/Summary

Skin : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Section 11. Toxicological information

Eyes : This product may irritate eyes upon contact.

Respiratory : High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. **Specific target organ toxicity (single exposure)**

Name	Category	Route of exposure	Target organs
methyl acetate	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
methanol	Category 1	Not determined	Not determined

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.

Skin contact : Defatting to the skin. May cause skin dryness and irritation.

Ingestion : Causes damage to organs following a single exposure if swallowed. Can cause central

nervous system (CNS) depression. Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue
dizziness/vertigo unconsciousness

: Adverse symptoms may include the following:
irritation
dryness
cracking

Skin contact : No specific data.

Ingestion

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

<i>Date of issue</i> / <i>Date of revision</i> : .	<i>Version</i> : 4.1	9/14

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
methyl acetate	Acute LC50 408000 µg/l Fresh water	Fish - Pimephales promelas Juvenile (Fledgling, Hatchling, Weanling)	96 hours
methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon Adult	48 hours
	Acute LC50 3289 to 4395 mg/l Fresh water	Daphnia - Daphnia magna Neonate	48 hours
	Acute LC50 290 mg/l Fresh water	Fish - Danio rerio - Egg	96 hours
vinyl acetate	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 8.81 mg/l	Algae - Pseudokirchnerella subcapitata	96 hours
	Acute EC50 12.6 mg/l	Daphnia	48 hours
	Acute LC50 10000 to 100000 µg/l Marine water	Crustaceans - Crangon crangon Larvae	48 hours

	Acute LC50 14000 µg/l Fresh water Chronic NOEC 1.58 mg/l	Fish - Pimephales promelas Algae - Pseudokirchnerella subcapitata	96 hours 96 hours
--	---	--	----------------------

Conclusion/Summary : Not available.

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
methanol	-	-	Readily
vinyl acetate	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
methyl acetate	0.18	-	low
methanol	-0.77	<10	low
vinyl acetate	0.73	3.16	low
6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol	6.25	549.54	high

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.







Date of issue/Date of revision : 01-03-2019

Version : 4.1

10/14

SRW Retaining Wall SP Adhesive

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	1133	1133	1133	1133	1133	1133
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (methyl acetate)	FLAMMABLE LIQUID, N.O.S. (methyl acetate)	FLAMMABLE LIQUID, N.O.S. (methyl acetate)	ADHESIVES, containing flammable liquid	FLAMMABLE LIQUID, N.O.S. (methyl acetate)	ADHESIVES, containing flammable liquid
Transport hazard class(es)	3 	3 	3 	3 	3 	3 
Packing group	III	III	III	III	III	III
Environmental hazards	No.	No.	No.	No.	No.	No.
Additional information	<u>Remarks</u> Limited quantity	<u>Remarks</u> Limited quantity	<u>Remarks</u> Limited quantity	<u>Special provisions</u> 640 (E) <u>Tunnel code</u> (D/E) <u>Remarks</u> Limited quantity	<u>Remarks</u> Limited quantity	<u>Remarks</u> Limited quantity

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) PAIR: methyl acetate : Not determined
TSCA 8(a) CDR Exempt/Partial exemption United States inventory : All components are listed or exempted.
(TSCA 8b):

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

SARA 302/304

Composition/information or ingredients

Section 15. Regulatory information

Name	%	EHS	SARA 302 TPQ		SARA 304 RQ	
			(lbs)	(gallons)	(lbs)	(gallons)
vinyl acetate	0.1 - 0.5	Yes.	1000	129	5000	644.8

SARA 304 RQ : 2658262.3 lbs / 1206851.1 kg [244116.6 gal / 924082 L]

SARA 311/312

Classification : Fire hazard
 Immediate (acute) health hazard
 Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
methyl acetate	25 - 50	Yes.	No.	No.	Yes.	No.
methanol	0.1 - 0.5	Yes.	No.	No.	Yes.	Yes.
vinyl acetate	0.1 - 0.5	Yes.	No.	No.	No.	Yes.
6,6'-di-tert-butyl-2,2'-methylene-diphenol	0 - 0.1	Yes.	No.	No.	No.	Yes.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	vinyl acetate	108-05-4	0.1 - 0.5
Supplier notification	vinyl acetate	108-05-4	0.1 - 0.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed. **State regulations**

Massachusetts : The following components are listed: METHYL ACETATE
New York : The following components are listed: Vinyl acetate
New Jersey : The following components are listed: METHYL ACETATE; ACETIC ACID, METHYL ESTER; VINYL ACETATE; ACETIC ACID ETHENYL ESTER
Pennsylvania : The following components are listed: ACETIC ACID, METHYL ESTER; ACETIC ACID ETHENYL ESTER

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
methanol	No.	Yes.	45000 µg/day (ingestion) 47000 µg/day (inhalation)	23000 µg/day (ingestion) 47000 µg/day (inhalation)

Section 15. Regulatory information

Canada Canadian lists

Canadian NPRI : None of the components are listed. **CEPA Toxic substances** : None of the components are listed.

Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.



Mexico

Classification :

Flammability

HealthReactivity

Special

International regulations

International lists

- Australia inventory (AICS)**: All components are listed or exempted.
- China inventory (IECSC)**: All components are listed or exempted.
- Japan inventory**: Not determined.
- Korea inventory**: All components are listed or exempted.
- Malaysia Inventory (EHS Register)**: Not determined.
- New Zealand Inventory of Chemicals (NZIoC)**: All components are listed or exempted.
- Philippines inventory (PICCS)**: All components are listed or exempted.
- Taiwan inventory (CSNN)**: All components are listed or exempted.

Europe : Not determined.

Chemical Weapons Convention List Schedule I Chemicals : Not listed

Chemical Weapons Convention List Schedule II Chemicals

: Not listed

Chemical Weapons Convention List Schedule III Chemicals

: Not listed

Chemical Weapons Convention List Schedule III Chemicals

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	2
Flammability	3
Physical hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Flammability

HealthInstability/Reactivity

Special

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

SRW Retaining Wall SP Adhesive

Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their

History

Date of printing

Date of issue/Date of revision Date of previous issue Version

Key to abbreviations

References

: 6/3/2015.

: 6/2/2015.

: 5/22/2015.

: 4.1

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United

Nations : Not available.

✔ Indicates information that has changed from previously issued version. **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

