

SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

MANUFACTURER: SRW Products
ADDRESS: 32020 126th Street
Princeton, MN 55371

EMERGENCY PHONE: 1-800-424-9300
INFORMATION PHONE: 1-800-752-9326
NAME OF PREPARER: Safety Director

Revision Date: 01-01-2024

PRODUCT NAME: Dual Wash
PRODUCT CODE: SSDW

SECTION 2 - HAZARDS IDENTIFICATION

HAZARD RISK CLASSIFICATION

SIGNAL WORD: DANGER

PICTOGRAM:

GHS05 - CORROSION GHS07 - EXCLAMATION MARK

HAZARD CLASS	HAZARD CATEGORY
CORROSIVE TO METALS	CATEGORY 1
SKIN CORROSION	CATEGORY 1 IRRITATION
TOXIC TO SPECIFIC TARGET ORGAN SINGLE EXPOSURE	CATEGORY 3 TOXICITY -

HAZARD STATEMENTS:

H290 May be corrosive to metal.
H303 May be harmful if swallowed
H314 Causes severe skin burns and eye damage
H335 May cause respiratory irritation

PRECAUTIONARY STATEMENTS: PREVENTION:

P234 Keep only in original packaging.
P260 Do not breath dusts/fume/gas/mist/vapors or spray.
P264 Wash hands and any exposed area thoroughly after handling. P271
Use only outdoors or in well-ventilated area.
P280 Wear protective impervious gloves/ OSHA approved eye protection/face
protection.

RESPONSE:

P301+P312 If swallowed: Call a Poison Center / doctor if you feel unwell.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse
skin with water (or shower).
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact
lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/ emergency responder. P312
Call a POISON CENTER/doctor if you feel unwell.
P321 Specific treatment (see on this label)
P330 Rinse mouth.
P363 Wash contaminated clothing before reuse. P390
Absorb spillage to prevent material damage.

STORAGE:

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405
Store locked up.
P406 Store in corrosive resistant/ . . . container with a resistant
inner liner.

DISPOSAL:

P501 Store separately. Dispose of contents/ container in accordance
with local/ regional/national /international regulations.

SAFETY DATA SHEET

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS NUMBER	WEIGHT	EXPOSURE LIMITS		
		PERCENT	OSHA PEL	ACGIH TLV	OTHER
Sodium Metasilicate Pentahyd	6834-92-0	10-25			2 MG/M3

PRIMARY ROUTES OF EXPOSURE:

Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Corrosive to eyes. Contact with eyes may cause severe irritation and burns.

SKIN: Corrosive to skin and mucous membranes. Contact with skin may cause severe irritation and burns. May be absorbed through skin in toxic amounts.

INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful. **CHRONIC**

HEALTH EFFECTS:

No anticipated chronic effects. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

SECTION 4 - FIRST AID MEASURES

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing. **INGESTION:**

If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: No flash

METHOD USED: n/a

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a

UPPER: n/a

EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

STORAGE INFORMATION:

Keep from freezing; material may coagulate. The minimum recommended storage temperature is 34F/1C, the maximum recommended storage temperature is 120F/49C. Keep away from incompatible materials (see section 10). Keep containers tightly closed. It is advised that material be used within 1 year of manufacture, rotate stock.

OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

SAFETY DATA SHEET

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION:

General room ventilation is adequate.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

COLOR: Various colors

ODOR: Amine or ammonia odor

SOLUBILITY IN WATER: Dilutable

SPECIFIC GRAVITY (H₂O=1): 1.12

VAPOR DENSITY: Heavier than air.

BOILING RANGE:

EVAPORATION RATE: Slower than nBuAc

COATING V.O.C.: 0 g/l (0.0 lb./gal)

SECTION 10 - STABILITY AND REACTIVITY DATA

STABILITY:

Stable under normal conditions and handling.

CONDITIONS TO AVOID:

None known

INCOMPATIBILITY (MATERIALS TO AVOID):

None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

HAZARDOUS POLYMERIZATION:

Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

SENSITIZATION:

None known.

CARCINOGENICITY:

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity. There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

SECTION 12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA:

Contains ammonia or amines which may be toxic to aquatic life.

SECTION 13 - DISPOSAL CONSIDERATIONS

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

SAFETY DATA SHEET

SECTION 14 - TRANSPORT INFORMATION

SHIPPING NAME:

UN1719, Caustic Alkali Liquids, N.O.S., (Disodium Trioxosilicate, Pentahydrate), 8, III

SECTION 15 - REGULATORY INFORMATION

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory. This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR

372) above de minimis concentrations.

STATE SPECIFIC REQUIREMENTS:

This product does not contain a chemical known to the state of California to cause cancer, birth defects or reproductive harm, subject to the requirements of California Proposition 65.

STATE LISTED COMPONENTS	CAS NUMBER	STATE CODE	.
-------------------------	------------	------------	---

SECTION 16 - OTHER INFORMATION

REVISION DATE: 11/16/88

HMIS CODES: H	F	R	P
1	0	0	B