

Safety Data Sheet

SRW Vertical Instant Lock Adhesive

Section 1. Identification

GHS product identifier: SRW Vertical Instant Lock Adhesive
Chemical name: Product type: SRW Vertical Instant Lock Adhesive
Liquid
Address: SRW Products
32005 126th Street
PO Box 70
Princeton, MN 55371
SRW Products Technical Services
Contact person: 800-752-9326
Telephone: 800-424-9300- Chemtrec
In case of emergency: AVIL 10/28
Product code: 01-01-2024
Date of revision: 01-01-2024
Print date: Adhesive
Chemical Family:

Relevant identified uses of the substance or mixture and uses advised against Not applicable.

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication

Standard

(29 CFR 1910.1200).

Classification of the substance or mixture : CARCINOGENICITY (inhalation) - Category 1B
TOXIC TO REPRODUCTION (Fertility) - Category 2
TOXIC TO REPRODUCTION (Unborn child) - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 38%

GHS label elements

Hazard pictograms :

| | | | | | | | | |
|---------------------------------------------------------------------------------------------------------------------------|------------|----------------|---------|------------------------|---|---|---|---|
| calcium carbonate | 471-34-1 | Not available. | 10 - 25 | - | 2 | 0 | 0 | - |
| 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich titanium dioxide trimethoxyvinylsilane stearic acid | 68515-48-0 | Not available. | 10 - 25 | - | 1 | 1 | 0 | - |
| | 13463-67-7 | UN3077 | 1 - 5 | 5000 mg/m ³ | 1 | 0 | 0 | - |
| | 2768-02-7 | UN1993 | 1 - 5 | - | 1 | 3 | 0 | - |
| | 57-11-4 | Not available. | 1 - 5 | - | 2 | 1 | 0 | - |
| Limestone | 1317-65-3 | Not available. | 10 - 25 | - | 0 | 0 | 0 | - |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact:** No known significant effects or critical hazards.
- Inhalation** Exposure to decomposition products may cause a health hazard. Serious effects maybe delayed following exposure.
- Skin contact:** No known significant effects or critical hazards.
- Ingestion:** No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact:** No specific data.
- Inhalation:** Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
- Skin contact:** Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
- Ingestion:** Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments:** No specific treatment
- Protection of first-aiders:** No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media:** Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media:** None known.
- Specific hazards arising:** In a fire or if heated, a pressure increase will occur and the container may burst.
- from the chemical**

- Hazardous thermal:** Decomposition products may include the following materials:
decomposition products carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

- Special protective actions** Promptly isolate the scene by removing all persons from the vicinity of the
incident

for fire-fighters

if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters mode.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency: personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders :

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions:
drains

Avoid dispersal of spilled material and runoff and contact with soil, waterways, and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill:

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill:

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages

into

an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain

special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing.

Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator.

Keep in the original container or an approved alternative made from a compatible material, kept

tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general: Eating, drinking and smoking should be prohibited in areas where this material is handled,

Occupational hygiene stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering areas. See also Section 8 for additional information on hygiene measures.

eating

Conditions for safe storage: Store in accordance with local regulations. Store in original container protected from direct

including any sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section

Incompatibilities 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready

avoid for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to environmental contamination

Section 8. Exposure controls/personal protection

Control parameters

United States Occupational exposure limits

| Ingredient name | Exposure limits |
|-----------------|-----------------|
|-----------------|-----------------|

| | |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| calcium carbonate | OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 3/2015). TWA: 10 mg/m ³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m ³ 8 hours. Form: Total dust OSHA PEL (United States, 2/2013). TWA: 15 mg/m ³ 8 hours. Form: Total dust OSHA PEL Z3 (United States, 2/2013). TWA: 250 MPPCF / (%SiO ₂ +5) 8 hours. Form: Respirable TWA: 10 MG/M3 / (%SiO ₂ +2) 8 hours. Form: Respirable ACGIH TLV (United States, 3/2015). TWA: 0.025 mg/m ³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2013). TWA: 0.05 mg/m ³ 10 hours. Form: respirable dust OSHA PEL 1989 (United States, 3/1989). Notes: as quartz TWA: 0.1 mg/m ³ , (as quartz) 8 hours. Form: Respirable dust |
| titanium dioxide | |
| crystalline silica, respirable powder | |

Canada

| Occupational exposure limits | | TWA (8 hours) | | | STEL (15 mins) | | | Ceiling | | | |
|-------------------------------------|------------------|----------------------|-------------------------|--------------|-----------------------|-------------------------|--------------|----------------|-------------------------|--------------|------------------|
| Ingredient | List name | ppm | mg/m³ | Other | ppm | mg/m³ | Other | ppm | mg/m³ | Other | Notations |
| | | | | | | | | | | | |

| | | | | | | | | | | | |
|---------------------------------------|-----------------|---|-------|---|----|----|---|---|---|---|-----|
| Limestone | AB 4/2009 | - | 10 | - | - | - | - | - | - | - | [3] |
| | BC 5/2015 | - | 3 | - | - | - | - | - | - | - | [a] |
| titanium dioxide | | - | 10 | - | - | - | - | - | - | - | [b] |
| | | - | - | - | - | 20 | - | - | - | - | [c] |
| | QC 1/2014 | - | 10 | - | - | - | - | - | - | - | [c] |
| | US ACGIH 3/2015 | - | 10 | - | - | - | - | - | - | - | [3] |
| | AB 4/2009 | - | 10 | - | - | - | - | - | - | - | [a] |
| | BC 5/2015 | - | 3 | - | - | - | - | - | - | - | [b] |
| trimethoxyvinylsilane | | - | 10 | - | - | - | - | - | - | - | [d] |
| | ON 7/2015 | - | 10 | - | - | - | - | - | - | - | [c] |
| | QC 1/2014 | - | 10 | - | - | - | - | - | - | - | [c] |
| | ON 7/2015 | - | - | - | 10 | 60 | - | - | - | - | [e] |
| | ON 7/2015 | - | 10 | - | - | - | - | - | - | - | [e] |
| stearic acid | US ACGIH 3/2015 | - | 0.025 | - | - | - | - | - | - | - | [f] |
| | AB 4/2009 | - | 0.025 | - | - | - | - | - | - | - | [g] |
| | BC 5/2015 | - | 0.025 | - | - | - | - | - | - | - | [h] |
| | ON 7/2015 | - | 0.1 | - | - | - | - | - | - | - | [i] |
| | QC 1/2014 | - | 0.1 | - | - | - | - | - | - | - | [j] |
| crystalline silica, respirable powder | AB 4/2009 | - | 10 | - | - | - | - | - | - | - | [3] |
| | | - | 10 | - | - | - | - | - | - | - | [c] |

[3]Skin sensitization

Form: [a] Respirable dust [b] Total dust [c] Total dust. [d]total dust [e]Total particulate mass [f]Respirable fraction [g] Respirable particulate [h]Respirable [i]Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size-selective device that,

(a) Meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of

4 µm at 50 per cent collection efficiency. [j]Respirable dust.

Mexico

Occupational exposure limits

| Ingredient | Exposure limits |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Limestone titanium dioxide | NOM-010-STPS (Mexico, 9/2000). LMPE-PPT: 10 mg/m ³ 8 hours. LMPE-CT: 20 mg/m ³ 15 minutes. NOM-010-STPS (Mexico, 9/2000). Notes: as Ti LMPE- PPT: 10 mg/m ³ , (as Ti) 8 hours. LMPE-CT: 20 mg/m ³ , (as Ti) 15 minutes. |

Consult local authorities for acceptable exposure limits.

Appropriate engineering: enclosures, If user operations generate dust, fumes, gas, vapor, or mist, use process

Controls local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure: Emissions from ventilation or work process equipment should be checked to ensure

Controls they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures: before Wash hands, forearms, and face thoroughly after handling chemical products, eating, smoking, and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

safety Wash contaminated clothing before reusing. Ensure that eyewash stations and showers are close to the workstation location.

Eye/face protection: risk Safety eyewear complying with an approved standard should be used when a

mists, assessment indicates this is necessary to avoid exposure to liquid splashes, gases or dusts. If contact is possible, the following protection should be worn, the

unless assessment indicates a higher degree of protection: safety glasses with shields.

side-

Skin protection

Hand protection: should Chemical-resistant, impervious gloves complying with an approved standard

indicates
manufacturer, should
be worn at all times when handling chemical products if a risk assessment this
is necessary. Considering the parameters specified by the glove check during
use that the gloves are still retaining their protective properties. It

be noted that the time to breakthrough for any glove material may be different for
different glove manufacturers. In the case of mixtures, consisting of several
substances, the protection time of the gloves cannot be accurately estimated.

Body protection:

before

Personal protective equipment for the body should be selected based on the task
being performed and the risks involved and should be approved by a specialist
handling this product.

Other skin protection:

be

Appropriate footwear and any additional skin protection measures should be
selected based on the task being performed and the risks involved and should
approved by a specialist before handling this product.

Respiratory protection:

approved

must be

Use a properly fitted, air-purifying or air-fed respirator complying with an
standard if a risk assessment indicates this is necessary. Respirator selection
based on known or anticipated exposure levels, the hazards of the product and
the
safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

| | |
|-----------------------------------------------|-----------------------------------------------------------------|
| Physical state: | Liquid |
| Color: | White. To Various |
| Odor: | Not Available |
| Odor threshold: | Not Available |
| pH: | Not Available |
| Melting point: | Not Available |
| Boiling point: | Not Available |
| Flash point: | Closed cup: >93.3°C (>199.9°F) [Closed cup] |
| VOC (less water, less exempt solvents) | 4 g/l |
| density | Relative 1.53 |
| Solubility: | Insoluble in the following materials: cold water and hot water. |

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous: Under normal conditions of storage and use, hazardous reactions will not occur.

Reactions

Conditions to avoid: No specific data.

Incompatible materials: No specific data.

Hazardous decomposition: Under normal conditions of storage and use, hazardous decomposition products should not

Products be produced.

Section 11. Toxicological information

Information on toxicological

effects acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|------------------------------------------------------------------------------------|-------------|---------|--------------|----------|
| calcium carbonate | LD50 Oral | Rat | 6450 mg/kg | - |
| 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich stearic acid | LD50 Oral | Rat | >10000 mg/kg | - |
| | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | 4600 mg/kg | - |

Conclusion/Summary: Not available.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|----------------------------------------------------------------------------------------|--------------------------|---------|-------|--------------------------------------|-------------|
| calcium carbonate | Eyes - Severe irritant | Rabbit | - | 24 hours 750 Micrograms | - |
| Skin - Moderate irritant | Skin - Moderate irritant | Rabbit | - | 24 hours 500 milligrams | - |
| 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich titanium dioxide | Eyes - Mild irritant | Rabbit | - | 0.1 Milliliters | - |
| | Skin - Mild irritant | Human | - | 72 hours 300 Micrograms Intermittent | - |
| trimethoxyvinylsilane | Eyes - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |

| | | | | | |
|--------------------------|--------------------------|--------|---|-------------------------------------|---|
| Skin - Mild irritant | Skin - Mild irritant | Rabbit | - | 24 hours 500 milligrams | - |
| stearic acid | Skin - Mild irritant | Human | - | 72 hours 75 milligrams Intermittent | - |
| Skin - Moderate irritant | Skin - Moderate irritant | Rabbit | - | 24 hours 500 milligrams | - |

Conclusion/Summary

Skin: Not available.

Eyes: Not available.

Respiratory: Not available.

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|---------------------------------------|------------|-------------------|---------------|
| crystalline silica, respirable powder | Category 1 | Inhalation | lungs |

Information on the likely: Not available **routes of exposure.**

Potential acute health effects

Eye contact: No known significant effects or critical hazards.

Inhalation: Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact: No known significant effects or critical hazards.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics **Eye contact:** No specific data.

Inhalation: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects: Not Available

Potential delayed effects: Not available.

Long term exposure

Potential immediate effects: Not available

Potential delayed effects: Not available.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|---------------------|
| calcium carbonate | Acute LC50 >56000 ppm Fresh water Chronic NOEC 61 mg/g Fresh water | Fish - Gambusia affinis - Adult Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours 28 days |
| titanium dioxide | Acute LC50 3 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 6.5 mg/l Fresh water | Daphnia - Daphnia pulex - Neonate | 48 hours |
| | Acute LC50 >1000000 µg/l Marine water | Fish - Fundulus heteroclitus | 96 hours |

Conclusion/Summary: Not available.

Persistence and degradability Not available.

Bio accumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-----------------------------------------------------------------------|--------------------|------------|-----------|
| 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich | 8.8 | <3 | low |
| titanium dioxide | - | 352 | low |
| stearic acid | 8.23 | 238 to 288 | low |

Other adverse effects: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of disposal with environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste material contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | ADR/RID | IMDG | IATA |
|----------------------------|--------------------|--------------------|-----------------------|----------------|----------------|----------------|
| UN number | Not available. | Not available. | Not available. | Not available. | Not available. | Not available. |
| UN proper shipping name | Not available. | Not available. | Not available. | Not available. | Not available. | Not available. |
| Transport hazard class(es) | Not available. | Not available. | Not available. | Not available. | Not available. | Not available. |
| Packing group | - | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. | No. |
| Additional information | - | - | - | - | - | - |

Special precautions for user:
are

in

Transport within user's premises: always transport in closed containers that upright and secure. Ensure that persons transporting the product know what to do the event of an accident or spillage.

Transport in bulk according:
to Annex II of MARPOL
73/78 and the IBC Code

Not available.

Section 15. Regulatory information

U.S. Federal regulations:

TSCA 8(a) CDR Exempt/Partial exemption:
United States inventory (TSCA 8b):

Not determined
Not Determined

Clean Air Act Section 112:

(b) Hazardous Air Pollutants (HAPs)

Not Listed

Clean Air Act Section 602 Class I Substances:

Not Listed

SARA 302/304**Composition/information on ingredients**

No products were found. **SARA 304 RQ:** Not applicable.

SARA 311/312

Classification: Delayed (chronic) health hazard

Composition/information on ingredients

| Name | % | Fire hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|----------------------------------------------------------------------------------------|-----------|-------------|----------------------------|----------|---------------------------------|---------------------------------|
| calcium carbonate | 10 - 25 | No. | No. | No. | Yes. | No. |
| 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich titanium dioxide | 10 - 25 | No. | No. | No. | Yes. | No. |
| trimethoxyvinylsilane stearic acid | 1 - 5 | No. | No. | No. | No. | Yes. |
| crystalline silica, respirable powder | 1 - 5 | Yes. | No. | No. | Yes. | No. |
| | 1 - 5 | Yes. | No. | No. | No. | No. |
| | 0.1 - 0.5 | No. | No. | No. | No. | Yes. |

State regulations**Massachusetts:**

The following components are listed: CALCIUM CARBONATE; TITANIUM DIOXIDE

New York:

None of the components are listed.

New Jersey:

The following components are listed: CALCIUM CARBONATE; LIMESTONE; TITANIUM DIOXIDE; TITANIUM OXIDE (TiO₂); SILICA, QUARTZ; QUARTZ (SiO₂)

Pennsylvania:

QUARTZ

The following components are listed: LIMESTONE; TITANIUM OXIDE; QUARTZ DUST;

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

| Ingredient name | Cancer | Reproductive | No significant risk level | Maximum acceptable dosage level |
|----------------------------------------------------------------------------------------|--------|--------------|---------------------------|---------------------------------|
| 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich titanium dioxide | Yes. | Yes. | No. | No. |
| crystalline silica, respirable powder | Yes. | No. | No. | No. |
| | Yes. | No. | No. | No. |

Canada Canadian lists

Canadian NPRI: None of the components are listed. **CEPA Toxic substances:** None of the components are listed.

Canada inventory:

Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

Classification:

Health: 2
Flammability 1 **Reactivity**
0
Special NA

International regulations International lists:

| | |
|----------------------------------------------------|-----------------|
| Australia inventory (AICS): | Not determined. |
| China inventory (IECSC): | Not determined. |
| Japan inventory: | Not determined. |
| Korea inventory: | Not determined. |
| Malaysia Inventory (EHS Register): | Not determined. |
| New Zealand Inventory of Chemicals (NZIoC): | Not determined. |
| Philippines inventory (PICCS): | Not determined. |
| Taiwan inventory (CSNN): | Not determined. |
| Europe: | Not determined. |

Chemical Weapons Convention List Schedule I Chemicals: Not Listed Chemical

Weapons Convention List Schedule II Chemicals: Not Listed

Chemical Weapons Convention List Schedule III Chemicals: Not Listed

Hazardous Material Information System (U.S.A.)

| | |
|-------------------------|---|
| Health | 0 |
| Flammability | 0 |
| Physical hazards | 0 |
| | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health 2
Flammability 1
Instability/Reactivity 0
Special NA

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Key to abbreviations: ATE = Acute Toxicity

Estimate

BCF = Bio concentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

References: Not available.

 Indicates information that has changed from previously issued version.

 Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.