



TECHNICAL DATA SHEET

PRX Specialty Seal™ Paver Restore X-treme



NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: SRWProducts.com

DESCRIPTION

Restore old paver surfaces and add rich color with this pigmented sealer. The color reviving technology makes old pavers look new again by evening out irregularities among older pavers. Add protection with a high-gloss finish. This solvent-based sealer adds long lasting durability even in x-treme conditions. Can be used for residential or commercial applications. Can also be used on new pavers to enhance and prolong coloring and uniformity of the paver surface.

APPLICATIONS

- Concrete Pavers
- Projects include:
 - Driveways
 - Patios/Walkouts
 - Pool Decks
 - Exposed aggregate concrete
 - Stamped Concrete

PROPERTIES

- Restores faded pavers with color reviving technology
- High gloss, wet look, restoring pigmented sealer
- Highlights and preserves the natural pigments in the surface
- Percolates around exposed aggregate to even out irregularities and adds rich color
- Highly durable, long lasting protection for extreme conditions
- Recommended for driveways & commercial applications
- Provides superior protection against freeze/thaw cycles, deicing salts, and chemical erosion and efflorescence
- Designed for exterior use

COVERAGE

- Up to 250 sq. ft. per gallon (23.23 sq. m. per 3.78 liters). Coverage may vary depending on surface and application.

SRW Products
800-752-9326

32005 126th St.
PO Box 70
Princeton, MN 55371

SRWProducts.com

Revised: 10-15-2021

PRX Specialty Seal™ Technical Data Sheet

Page 1 of 3

USER TIPS

- **Test in an inconspicuous area before starting the general application to ensure desired results and expected finish. Always test prior to use because pigment within sealer could alter the final appearance.**
- If using on stamped concrete, test in a small discrete area before use to ensure desired results.
- Always follow hardscape manufacturer's sealing recommendations.
- For added slip resistance, use SRW SR Slip-Resist™. 2 coats are required, incorporate SRW Slip-Resist into the second coat only.
- Do not use more than one sealer on the same project unless it is HGX. SRW Products HGX High Gloss X-treme can be applied over this product.
- If wear patterns occur over time or if spillage removes the coating, Additional coats may be reapplied to the affected area(s).
- Refer to our specs and accessories chart for proper sprayer or accessory use
- Material will not freeze and may be stored outdoors in cold weather, however it must be allowed to warm to approximately 50°F before use.
- Not for use on:
 - ▶ Asphalt, clay pavers/brick, slate, sandstone/bluestone, slate or polished stone
 - ▶ Structures under hydrostatic pressure or permeable pavers
 - ▶ Concrete overlays
 - ▶ Vertical applications
 - ▶ Surfaces subjected to hydrostatic water pressure
 - ▶ Light colored pavers (Ivory, cream or light grey).
 - ▶ Always test prior to use because pigment within sealer could alter the final appearance.

INSTALLATION INSTRUCTIONS

CLEAN

1. Wait 28 days after installing polymeric sand before sealing.
2. Thoroughly sweep surface of joint sand or loose material.
3. Spot clean if needed with one of the SRW Specialty Clean™ products. Then, prepare surface with an SRW Products General Purpose Cleaner.

CLIMATE

4. After cleaning, wait at least 24 hours before sealing. Surface and joints must be completely dry.
5. Recommended application temperatures are 50°F - 80°F (10°C - 27°C) from installation through the cure process.
6. Do not apply if inclement weather is forecasted within 24 hours.

APPLY

7. **STIR THOROUGHLY. Be sure to stir prior to and during use. Due to pigment, PRX should be blended every 20 minutes.**
8. Apply with an SRW Products approved Slit Foam Roller and sprayer.
9. For best results, spray then back roll. This prevents an uneven finish. A 2-person application is recommended.
10. Start at the highest project elevation. Do not allow sealer to pool on surface or in joints.
11. Repeat if desired.

SRW Products

800-752-9326

32005 126th St.

PO Box 70

Princeton, MN 55371

SRWProducts.com

Revised: 10-15-2021

PRX Specialty Seal™ Technical Data Sheet

Page 2 of 3

CURE

12. Allow sealed area to dry and cure 24 hours.

13. Protect area from water and rain until dry.

Dry-tack free: 25 minutes

Foot traffic: 24 hours

Vehicle traffic: 72 hours

Note: All calculations based on 68°F – 77°F (20°C – 25°C)

STORAGE AND SHELF LIFE

Material will not freeze and may be stored outdoors in cold weather, however it must warm to approximately 50°F before use.

CLEAN UP

Clean sprayer and tools with SRW Specialty Clean XY Xylene Solvent.

WARNINGS

FIRST AID: EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention. SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing. INGESTION: DO NOT INDUCE VOMITING. Immediately administer 1-2 glasses of water and seek medical attention. INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

CAUTION: Protect buildings, landscaping and vehicles from overspray or spray drift.

WARNING: Do not inhale spray mist. Irritating to skin and eyes. Always wear a mask and protective eyewear and clothing. See SDS for further information.

HMIS RATING: Hazard Index 2=moderate hazard, 0=minimal hazard

Health 2, Flammability 2, Reactivity 0, Protection G

IMPORTANT NOTICE: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only. FOR PROFESSIONAL USE ONLY. Test in a small, discrete area before use.

SHIPPING: DOT Shipping name: Not Regulated

UN1263, Paint, 3, III

VOC 671 g/L (5.60 lbs/gallon)

PACKAGING

Specialty Seal™ PRX Paver Restore X-treme			
PART #	SIZE	AMT PER CTN	QUANTITY
SSPC PRX CTN	1 gal	4 CTNS	36 CTNS/PLT
SSPC PRX 5GAL	5 gal	1	36/PLT

SRW Products

800-752-9326

32005 126th St.

PO Box 70

Princeton, MN 55371

SRWProducts.com

Revised: 10-15-2021

PRX Specialty Seal™ Technical Data Sheet

Page 3 of 3