



Tel: 800-752-9326  
Fax: 763-389-2725  
SRWProducts.com

PO Box 70  
32005 126th St  
Princeton, MN 55371

## SRW SB2

To Whom It May Concern:

This letter is to certify that SRW Products Manufactures/Supplies a 100% Polyester Non-Woven Thermal Bonded Filament Fibers marketed as **SRW SB2**. With excellent dimensional stability and low shrinkage, our Spun Bond products serve as the professionals choice for landscape and geotextile projects. The fabric will not rot or mildew, is non-biodegradable with superior UV resistance, and is resistant to damage from insects and rodents.

**SRW SB2** meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Weight (Typical)	ASTM D 5261	oz/sy	2.0
Grab Tensile	ASTM D 4632	lbs.	66 x 68
Grab Elongation	ASTM D 4632	lbs.	48
Trap Tear	ASTM D 4533	lbs.	18
Puncture	ASTM D 4833	lbs.	28
Permittivity	ASTM D 4491	sec <sup>-1</sup>	Above 2.5
Water Flow	ASTM D 4491	gpm/ft <sup>2</sup>	208
AOS	ASTM D 4751	US Sieve	#50

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.