



TECHNICAL DATA SHEET

CDX Cleaner & Degreaser X-treme Specialty Clean



NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: SRWProducts.com

DESCRIPTION

Specialty Clean™ CDX is a concentrated spot treatment that removes grease, oil, tar, gum, rubber paint, and dirt from numerous surfaces.

APPLICATIONS

- Pavers
- Concrete
- Natural stone
- Brick
- Wetcast
- Masonry

PROPERTIES

- Fast-Working Oil & Grease Remover
- Removes Tar, Gum, Rubber and Paint
- Rinses with Water

COVERAGE

- Spot treatment specialty cleaner

USER TIPS

- Wear eye, skin and respiratory protection when applying.
- Test in an inconspicuous area before starting the general application to ensure desired results.

INSTALLATION INSTRUCTIONS

CLIMATE

1. Recommended application temperatures are 50°F - 80°F (10°C - 27°C)

APPLY

2. Apply to surface and allow solution to penetrate stain.
3. Let soak 5-10 minutes.

SCRUB

4. Scrub surface with a stiff bristle brush.

RINSE

5. Use a pressure washer multiple times to remove residue.
6. A SRW general purpose cleaner should be used prior to sealing.

STORAGE AND SHELF LIFE

- Store in an upright position out of direct sunlight. Will not freeze or be damaged by low temperatures. SHELF LIFE: 18 months.

CLEAN UP

Rinse off all equipment with soap and water and let dry.

WARNINGS

HMIS RATING: Hazard Index 2=moderate hazard, 0=minimal hazard
Health 2, Flammability 2, Reactivity 0, Protection B

CONTAINS D-LIMONENE. Harmful if swallowed. Irritating to skin and eyes.

FIRST AID: For eye contact, flush with water for at least 15 minutes. Wash exposed skin with warm, soapy water. If irritation persists, see a physician. If ingested, DO NOT INDUCE VOMITING. See a physician immediately.

IMPORTANT NOTICE: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.

SHIPPING: DOT Shipping name: Not Regulated.
VOC 638 g/L (5.32 lbs/gallon)

PACKAGING

PW Paver Wash		
PART #	SIZE	AMT PER CTN
SSCDX CTN 4	1 qt	4/CTN