



## TECHNICAL DATA SHEET

# PSX Premium Seal™

## Water-Based Penetrating X-treme Curing Compound



### NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: [SRWProducts.com](http://SRWProducts.com)

### DESCRIPTION

Our PSX Penetrating X-treme™ premium sealer protects and seals high-traffic and commercial areas while providing an invisible, natural-looking finish. This premium sealer can be applied horizontally and vertically, restoring pavers and retaining wall surfaces. Protect your surfaces from water intrusion, acid rain, deicing chemicals, and airborne pollutants with minimal effort.

### APPLICATIONS

- Concrete Pavers
- Concrete Permeable Pavers
- Clay Pavers
- Wetcast
- Block Retaining Walls
- Manufactured Stone

### PROPERTIES

- Invisible/Natural-Look Finish
- Restores and Protects
- Water-Based Formula
- Provides superior protection against freeze/thaw cycles, deicing salts, chemical erosion, and efflorescence
- Ideal for High-Traffic Areas
- Interior/Exterior Applications
- Highly durable/long lasting protection and enhancement
- Breathable

### CURING TIME

- Dry-tack free: 25 minutes.
- Foot traffic: 24 hours.
- Vehicle traffic: 72 hours.
- *Note: All calculations based on 68°F-77°F (20°C-25°C).*

### COVERAGE

<b>COVERAGE:</b> <i>Approximate Length of Bead</i>	
Size	Sq. Ft.
1gal	200
5 gal	1000 Sq. Ft.

SRW Products  
800-752-9326

32005 126th St.  
PO Box 70  
Princeton, MN 55371

[SRWProducts.com](http://SRWProducts.com)

Revised: 04-16-2024

PSX Penetrating X-treme™ Technical Data Sheet

Page 1 of 3

## USER TIPS

Test in an inconspicuous area before starting the general application to ensure desired results & expected finish.

Always follow hardscape manufacturer's sealing recommendations.

PSX is a **ONE** coat sealer. Additional coats may create an irregular appearance.

If using on manufactured stone, ask dealer about cleaning and sealing procedures prior to application.

- Do not use more than one sealer on the same project.

### Not for use on:

- slate, granite, travertine, sandstone, bluestone, or polished stone.
- structures under hydrostatic pressure.
- concrete overlays.

## INSTALLATION INSTRUCTIONS

### RECOMMENDED TOLS

For best results, use an SRW Heavy-Duty Construction Sprayer & a Slit Foam Roller to apply.

### CLEAN

- Wait 28 days after installing polymeric sand before sealing.
- Thoroughly sweep or blow the surface of joint sand or loose material.
- Spot clean if needed with CDX Cleaner & Degreaser X-treme™, RE Rust Eliminator™, OC Organic Cleaner™, or M3C Mold, Moss, and Mildew cleaner™.
- Then prepare all surfaces with EF Efflorescence™, PW Paver Wash™ or DW Dual Wash™.

### CLIMATE

- After cleaning, wait at least 24 hours before sealing. Surface and joints must be completely dry.
- Recommended application temperatures are 50°F-80°F (10°C-27°) from installation through the cure process.
- Do *not* apply if inclement weather is forecasted within 24 hours.

### APPLY

- It's important to **stir thoroughly** before application.
- Apply with an SRW Products-approved Slit Foam Roller and sprayer.
- Spray, then back roll. This prevents an uneven finish.
  - A 2-person application is recommended.
- Always spray against a wet edge and do not overlap a previously sealed and dried area.
- Start at the highest project elevation
- Do not allow sealer to pool on pavers or in joints

### CURE

- Allow the sealed area to dry and cure for 24 hours.
- Protect the area from water and rain until dry.
- Curing time ranges:
  - Dry-tack free: 25 minutes.
  - Foot traffic: 24 hours.
  - Vehicle traffic: 72 hours.
  - Note: All calculations based on 68°F-77°F (20°C-25°C).

## CLEANING

- Clean sprayer and tools with soap and warm water.

## STORAGE AND SHELF LIFE

Store in a cool, well-ventilated area with cap or lid firmly in place.

KEEP FROM FREEZING

SRW Products  
800-752-9326

32005 126th St.  
PO Box 70  
Princeton, MN 55371

SRWProducts.com

Revised: 04-16-2024

PSX Penetrating X-treme™ Technical Data Sheet

Page 2 of 3

## WARNINGS

**FIRST AID:** Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention. **SKIN CONTACT:** Wash contaminated area with soap and water. Remove and launder contaminated clothing. **INGESTION:** If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention. **INHALATION:** Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

**IN CASE OF FIRE:** Use CO<sub>2</sub> or dry chemical extinguisher. Do not use water spray.

**CAUTION:** Protect buildings, landscaping and vehicles from overspray or spray drift.

**WARNING:** Do not inhale spray mist. Irritating to skin and eyes. Always wear a mask and protective eyewear and clothing. Keep container closed when not in use. If spilled, eliminate all sources of ignition. Contain spilled material and remove with inert absorbent using non-sparking tools. Dispose of contaminated absorbent, container, and unused contents in accordance with all applicable regulations.

**HMIS RATING:** Hazard Index 2=moderate hazard, 0=minimal hazard

Health 2, Flammability 0, Reactivity 0, Protection G

**IMPORTANT NOTICE:** Water (7732-18-5), Alkoxy Silanes (Proprietary CAS), Ethyl Alcohol (64-17-5), Polydimethylsiloxane (Proprietary CAS). Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only. FOR PROFESSIONAL USE ONLY. Test in a small, discrete area before use.

## TRANSPORT

For more information on the proper handling and transportation of this product, please refer to the latest version of the Safety Data Sheet (SDS). Visit [SRWProducts.com](http://SRWProducts.com) for an up-to-date version of this product's Safety Data Sheet (SDS).

## PACKAGING

PSX SEALER			
PART#	SIZE	AMT PER CTN	QUANTITY
SSPC PSX CTN	1 GAL	4/CTN	36 CTN/PLT
SSPC PSX 5GAL	5 GAL	1	36/PLT

### SRW Products

800-752-9326

32005 126th St.

PO Box 70

Princeton, MN 55371

[SRWProducts.com](http://SRWProducts.com)

Revised: 04-16-2024

PSX Penetrating X-treme™ Technical Data Sheet

Page 3 of 3