



TECHNICAL DATA SHEET

PW Paver Wash

Paver Cleaner



NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: SRWProducts.com

DESCRIPTION

A general-purpose paver wash. It is a must-use product to prepare pavers for sealing. This multi-purpose wash can tackle polyhaze, efflorescence and ground-in dirt. PW can easily be applied to pavers, retaining walls, brick and masonry, and should be used after spot cleaning.

APPLICATIONS

- Concrete Pavers
- Clay Pavers

PROPERTIES

- Opens surface pores for optimal bond with sealer
- Restores original paver color
- Contains no muriatic acid or hydrochloric acid
- Removes polyhaze, efflorescence and ground-in dirt

COVERAGE

COVERAGE	
Size	Sq. Ft.
1 gal	200 Sq. Ft.
5 gal	1,000 Sq. Ft.

USER TIPS

- Wear eye, skin and respiratory protection when applying.
- Test in an inconspicuous area before starting the general application to ensure desired results.
- Wait 60-90 days for new pavers to cure before applying PW.
- Prolonged contact of cleaner on metal or other surfaces may result in etching or damage.
- Saturate vegetation before and after application of PW.

INSTALLATION INSTRUCTIONS

PREPARATION

1. Thoroughly sweep surface of joint sand, dust, debris or loose material.
2. Spot clean if needed with one of these SRW Specialty Clean™ products: *CDX Cleaner & Degreaser X-treme*, *MC Mold, Moss & Mildew Cleaner*, *OC Organic Stain Cleaner*
3. Recommended application temperatures are 50°F - 80°F (10°C - 27°C)

SRW Products

800-752-9326

32005 126th St.
PO Box 70
Princeton, MN 55371

SRWProducts.com

Revised: 03-22-2021

PW Paver Wash Technical Data Sheet

Page 1 of 2

WET

4. Saturate surface & surrounding area (including vegetation) thoroughly with water.
5. Do not allow product to dry on surface. Re-spray with water, if needed, to keep area wet. A 2-person application is recommended.

APPLY

6. Apply PW directly to surface with a sprinkler can. Do not dilute.
7. Scrub with a stiff bristle brush. Let sit for 5 minutes. Keep wet. Rescrub.
8. For large areas, work in 200 sq. ft. (18.58 sq. m.) sections.
9. If working on an incline, start at the highest point, working in small sections. Scrub from the bottom of the section, pushing excess PW Paver Wash up over job.

RINSE

10. Immediately rinse surface & surrounding areas (including vegetation) thoroughly with clean water until all traces of cleaner are gone.
11. Repeat if necessary. Let dry.
12. Wait 24 hours before applying an SRW sealer.

STORAGE AND SHELF LIFE

KEEP FROM FREEZING. Store container in a cool area with cap or lid firmly in place.

CLEAN UP

Rinse off all equipment with soap and water and let dry.

WARNINGS

WARNING: CONTAINS SULFAMIC ACID. Avoid contact to skin, eyes and clothing.

FIRST AID: Wash with warm soapy water if skin contact occurs. For any eye contact, flush immediately and thoroughly with clean water for 15 minutes and seek medical attention. Do not mix with any other materials/liquids except water.

IMPORTANT NOTICE: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.

SHIPPING DOT Shipping name: UN2967, Sulfamic Acid, 8, III
VOC 0 g/L (0 lbs/gallon)

PACKAGING

PW Paver Wash			
PART #	SIZE	AMT PER CTN	QUANTITY
SSPW CTN	1 gal	4/CTN	36 CTNS/PLT
SSPW 5GAL	5 gal	1	36/PLT

SRW Products

800-752-9326

32005 126th St.

PO Box 70

Princeton, MN 55371

SRWProducts.com

Revised: 03-22-2021

PW Paver Wash Technical Data Sheet

Page 2 of 2