



TECHNICAL DATA SHEET

S-PS VOC Specialty Seal™

Natural Stone Solvent-Based Penetrating Cure & Seal



NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: SRWProducts.com

DESCRIPTION

S-PS Penetrating Specialty Seal is a natural-looking penetrating sealer that can be used on a variety of surfaces for both vertical and horizontal applications. It protects the surface against damaging effects of weather, deicing chemicals, oils, food and more. It is easy to apply and retains the original appearance of granite, bluestone, sandstone, limestone, marble, travertine and manufactured stone.

APPLICATIONS

- Concrete Pavers
- Granite/Quartz
- Marble/Travertine
- Limestone
- Bluestone/Sandstone

PROPERTIES

- Invisible/natural-look finish
- Protects surface from staining
- Ideal for outdoor applications
- Minimizes salt and freeze/thaw damage
- Solvent based

COVERAGE

COVERAGE	
Size	Sq. Ft.
1 gal	200 Sq. Ft.
5 gal	1000 Sq. Ft.

USER TIPS

- Test in an inconspicuous area before starting the general application to ensure desired results and expected finish.
- Always follow hardscape manufacturer's sealing recommendations.
- If using on manufactured stone, ask dealer about cleaning and sealing procedures prior to application.
- Do not use more than one sealer on the same project.

INSTALLATION INSTRUCTIONS

CLEAN

1. Wait 28 days after installing polymeric sand before sealing.
2. Thoroughly sweep surface of joint sand or loose material.

SRW Products
800-752-9326

32005 126th St.
PO Box 70
Princeton, MN 55371

SRWProducts.com

Revised: 03-22-2021

SPS VOC Specialty Seal™ Technical Data Sheet

Page 1 of 3

3. Spot clean if needed with one of the SRW Specialty Clean™ products. Then, prepare surface with an SRW Products General Purpose Cleaner.

CLIMATE

4. After cleaning, wait at least 24 hours before sealing. Surface and joints must be completely dry.
5. Recommended application temperatures are 50°F - 80°F (10°C - 27°C) from installation through the cure process.
6. Do not apply if inclement weather is forecasted within 24 hours.

APPLY

7. STIR THOROUGHLY.
8. Apply with an SRW Products approved Slit Foam Roller and sprayer.
9. For best results, spray then back roll. This prevents an uneven finish. A 2-person application is recommended.
10. Start at the highest project elevation. Do not allow sealer to pool on surface or in joints.
11. Repeat if desired.

CURE

12. Allow sealed area to dry and cure 24 hours.
13. Protect area from water and rain until dry.

Dry-tack free: 25 minutes

Foot traffic: 24 hours

Vehicle traffic: 72 hours

Note: All calculations based on 68°F – 77°F (20°C – 25°C)

STORAGE AND SHELF LIFE

Keep from freezing. Store container in a cool area with cap or lid firmly in place.

CLEAN UP

Clean sprayer and tools with soap and warm water.

WARNINGS

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately. Remove contact lenses, if present and easy to do so. If on skin (or hair), immediately take off all contaminated clothing. Wash skin thoroughly with soap and water. If irritation persists, see a physician. Wash contaminated clothing before reuse. If swallowed, DO NOT INDUCE VOMITING. Give conscious victim 1 to 2 glasses of water and get medical attention immediately.

IN CASE OF FIRE: Use CO2 or dry chemical extinguisher. Do not use water spray.

CAUTION: Protect buildings, landscaping and vehicles from overspray or spray drift.

WARNING: Do not inhale spray mist. Irritating to skin and eyes. Always wear a mask and protective eyewear and clothing. Keep container closed when not in use. If spilled, eliminate all sources of ignition. Contain spilled material and remove with inert absorbent using non-sparking tools. Dispose of contaminated absorbent, container, and unused contents in accordance with all applicable regulations.

HMIS RATING: Hazard Index 2=moderate hazard, 0=minimal hazard

Health 2, Flammability 3, Reactivity 0, Protection 1

CONTAINS PETROLEUM DISTILLATES. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES

EYE, SKIN, NOSE, AND THROAT IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. HARMFUL IF SWALLOWED. DO NOT TAKE INTERNALLY.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and various system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. See SDS for further information. Keep away from heat, sparks, and flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe vapors or spray mists. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's direction for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

IMPORTANT NOTICE: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only. FOR PROFESSIONAL USE ONLY. Test in a small, discrete area before use.

SHIPPING: DOT Shipping name: UN1139, Coating Solution, 3, II
Concrete curing & sealing compound coating VOC 583 g/L (4.86 lbs/gallon)

PACKAGING

Specialty Seal™ S-PS VOC Penetrating			
PART #	SIZE	AMT PER CTN	QUANTITY
STONE S-PS VOC CTN	1 gal	4/CTN	36 CTNS/PLT
STONE S-PS VOC 5GAL	5 gal	1	36/PLT