



TECHNICAL DATA SHEET

SS Sealer Stripper Specialty Clean™



NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: SRWProducts.com

DESCRIPTION

Specialty Clean™ SS Sealer Stripper is an industrial strength, biodegradable stripper that removes many types of sealer and curing compounds, graffiti, tile and carpet adhesives, dry fog paints, etc.

APPLICATIONS

- Graffiti/Dry Fog Paints
- Tile/Carpet Adhesive
- Aids in removal of sealing and curing compounds

PROPERTIES

- Industrial strength
- Biodegradable

COVERAGE

- Up to 200 sq. ft. per gallon (18.58 sq. m. per 3.78 liters).
- Coverage may vary depending on surface and application.

INSTALLATION INSTRUCTIONS

CLIMATE

1. Product is supplied ready to use. No stirring or thinning is required. Before using this product, thoroughly read product's label and Safety Data Sheet (SDS). Test in an inconspicuous area before starting the general application to ensure desired results. Recommended application temperatures are 50°F - 80°F (10°C - 27°C).

APPLY

2. Work in small areas (no larger than 10 sq. ft./93 sq.m.). Apply to dry pavers. Product may be applied to both vertical or horizontal surfaces by brush at a rate of approximately 200 sq. ft./gallon (18.58 sq. m./3.78 liters).

WAIT

3. Allow 10 minutes for the stripper to soak into and soften the coating for removal.

SCRUB

4. Lightly scrub the surface with a natural bristle broom to remove stubborn areas. Use high-pressure wash to remove the stripper and coating. Difficult areas may need a second treatment. Sealer will readhere if not completely removed.

STORAGE AND SHELF LIFE

Store container in a cool area with cap or lid firmly in place.

SRW Products
800-752-9326

32005 126th St.
PO Box 70
Princeton, MN 55371

SRWProducts.com

Revised: 03-22-2021

SS Sealer Stripper Specialty Clean™ Technical Data Sheet

Page 1 of 2

WARNINGS

CAUTION. Protect buildings, landscaping and vehicles from overspray or spray drift. Contact with concentrated product will soften or etch many common plastics and kill vegetation.

WARNING: Keep away from heat, sparks, and flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe vapors or spray mists. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If swallowed, DO NOT INDUCE VOMITING. Give conscious victim 1–2 glasses of water and get medical attention immediately.

SPILLS/DISPOSAL: Keep container closed when not in use. If spilled, eliminate all sources of ignition. Contain spilled material and remove with inert absorbent using non-sparking tools. Dispose of contaminated absorbent, container, and unused content in accordance with all applicable regulations. Empty container may contain explosive and harmful vapors and residue. Keep away from heat, sparks and flames.

IN CASE OF FIRE: Use CO₂ or dry chemical extinguisher. Do not use water spray.

IMPORTANT NOTICE: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only. For information and installation instructions visit, SRWproducts.com.

HAZARDOUS INGREDIENTS

C.A.S.

D-Limonene	5989-27-5
Dimethyl Glutarate	1119.40.0
N-Methyl-2-Pyrrolidone	872-50-4
Dimethyl Adipate	627-93-0
Dimethyl Succinate	106-65-0

HMIS RATING: Hazard Index 2=moderate hazard, 0=minimal hazard
Health 2, Flammability 2, Reactivity 0, Protection G

SHIPPING: DOT Shipping name: Not regulated
VOC 975 g/L (8.14 lbs/gallon)

PACKAGING

Specialty Clean™ SS Sealer Stripper			
PART #	SIZE	AMT PER CTN	QUANTITY
SSS STRIPPER CTN	1 gal	4/CTN	36 CTNS/PLT
SSS STRIPPER5	5 gal	1	36/PLT

SRW Products

800-752-9326

32005 126th St.
PO Box 70
Princeton, MN 55371

SRWProducts.com

Revised: 03-22-2021

SS Sealer Stripper Specialty Clean™ Technical Data Sheet

Page 2 of 2