



TECHNICAL DATA SHEET

SEAMS RIGHT TURF ADHESIVE™

NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: SRWProducts.com

DESCRIPTION

Our Seams Right™ Turf Adhesive is the ideal choice for all your turf adhesive needs. Its moisture-curing formula ensures a secure, long-lasting seam every time.



APPLICATIONS

- Synthetic Turf
- Putting Greens
- Pet Areas
- Playgrounds
- Landscaping

PROPERTIES

- Moisture Curing
- Weather Resistant
- Fast Setting
- Interior/Exterior
- VOC Compliant

WORKING TIME

- 45 minutes

CURE TIME

- 60-120 minutes, full cure 24-48 hours.

COVERAGE

- 3/8" Bead = 35'

USER TIPS

- Peel back seam just before applying adhesive to tape. The turf backing can heat up and expand, leaving unwanted gaps at seams when the turf cools.

CURING

Protect turf from rain/water and freezing conditions for 12 hours after installation. Protect from light foot traffic for 12 hours, and heavy foot traffic for 24 hours.




CLEAN UP

Clean uncured adhesive with mineral spirits.

STORAGE AND SHELF LIFE

Store at room temperature, no freezing weather. Will freeze or be damaged by low temperatures.
12 month shelf life

INSTALLATION INSTRUCTIONS



1. Follow manufacturer's recommendations for site preparation and rolling out turf. For proper adhesion surfaces must be flat, completely dry, and above 40°F.
2. Make sure the surfaces being bonded are clean of any materials that may prevent proper adhesion like dust, loose turf fibers, moisture, or frost.
3. Peel back turf at seam to make space for laying Seams Right™ Turf Tape. Unroll turf tape to full length of seam.
4. Cut nozzle tip at slant for a 3/8" bead. Puncture inner foil.
5. With a minimum 10:1 thrust ratio, apply using SRW Products Standard or Premium Caulking Gun. Liberally apply Seams Right™ Adhesive onto turf tape in a zig-zag pattern, no more than 1½" distance between lines. Stay 3/4" away from the edge of turf tape.
6. Tightly join turf edges together onto Seams Right™ Turf Adhesive and Tape. Using a weighted roller, pass over seam multiple times to compress turf into Adhesive and Tape.


WARNINGS

DANGER: IRRITANT. MAY IRRITATE SKIN, EYES, OR RESPIRATORY TRACT. CONTAINS POTENTIAL SENSITIZER. MAY CAUSE ALLERGIC SKIN OR RESPIRATORY REACTIONS. MAY BE HARMFUL IF SWALLOWED OR INHALED. READ WARNING STATEMENT ON CASE LABEL BEFORE USE.

May cause allergy or asthma symptoms or breathing difficulties. If inhaled Do not breathe fumes. Do not get in eyes, on skin or on clothing. Do not swallow. Use only in a well ventilated area or wear mask. Wash thoroughly after handling. Store container in a cool, dry area with lid tightly sealed. Do not reuse container.

KEEP OUT OF THE REACH OF CHILDREN. FIRST

AID TREATMENT: Contains Phthalates, Methylene Diphenyl Isocyanate (MDI), Carbon Black and Titanium Dioxide inextricably bound in a polymer matrix. If in eyes or on skin, rinse with water for at least 15 minutes. If on clothes, remove clothes. If breathed in, move person to fresh air. If swallowed, call a Poison Control Center or doctor immediately.

 **WARNING:** This product can expose you to chemicals including Quartz, which is known to the State of California to cause cancer, and Methyl alcohol which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

TRANSPORT

For more information on the proper handling and transportation of this product, please refer to the latest version of the Safety Data Sheet (SDS). Visit SRWProducts.com for an up-to-date version of this product's Safety Data Sheet (SDS).

PACKAGING

SEAMS RIGHT™ TURF ADHESIVE		
PART#	SIZE	AMT PER CTN
ATURF 28	28 OZ	12/CTN

IMPORTANT NOTICE: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only. For professional use only. Test in a small, discrete area before use sand from surface of the project.