



## TECHNICAL DATA


### SiteDrain Sheet Series 90/110/180

#### Installation Guides

- Vertical Applications
- Retaining Walls
- Foundation Walls

#### Other Information

- Fittings and Accessoires
- Packaging and Storage




# SITEDRAIN™ SHEET 90 SERIES

## PREFABRICATED SHEET DRAIN



### PRODUCT OVERVIEW



SITEDRAIN Sheet 90 Series geocomposite sheet drain products are composed of a dimpled polymeric core with a geotextile bonded to the dimple side. The geotextile allows water to pass through while retaining backfill materials. The solid core allows water collection from one side and provides a continuous flow path to designated drainage exits.

SITEDRAIN Sheet 90 Series products provide an economical solution for single-sided subsurface drainage applications requiring moderate strength and moderate flow capacity. Various geotextile options are available to meet project-specific requirements.

PROPERTY <sup>1</sup>	TEST METHOD	UNIT OF MEASURE	93	94	94-T	96	96-W	98
<b>GEOTEXTILE</b>								
Material <sup>2</sup>			PP, NPNW	PP, NPNW	PP, SBNW	PP, NPNW	PP, WM	PP, NPNW
Survivability	AASHTO M288	Class	-	3	3	2	-	1
Grab Tensile Strength	ASTM D4632	lbs	100	135	150	195	430 x 240	245
		N	445	601	667	867	1,914 x 1,068	1,090
Grab Elongation	ASTM D4632	%	70	60	50	60	30 x 15	60
CBR Puncture	ASTM D6241	lbs	305	365	295	505	800	580
		N	1,356	1,624	1,312	2,246	3,560	2,580
Trapezoidal Tear	ASTM D4533	lbs	50	60	70	85	180 x 130	100
		N	222	267	310	378	801 x 579	445
UV Resistance	ASTM D4355	% / 500 Hrs	70	70	70	70	90	70
Apparent Opening Size (AOS) <sup>3</sup>	ASTM D4751	sieve	70	70	80	70	50	80
		mm	0.212	0.212	0.180	0.212	0.300	0.180
Permittivity	ASTM D4491	sec <sup>-1</sup>	2.7	2.4	1.0	2.1	2.7	1.8
Water Flow Rate	ASTM D4491	gpm / ft <sup>2</sup>	165	175	70	155	195	135
		Lpm / m <sup>2</sup>	6,724	7,130	2,850	6,315	7,944	5,501
<b>CORE</b>								
Compressive Strength	ASTM D6364	psf	9,000	9,000	9,000	9,000	9,000	9,000
	ASTM D1621	kPa	431	431	431	431	431	431
Thickness	ASTM D5199	in	0.25	0.25	0.25	0.25	0.25	0.25
		mm	6.35	6.35	6.35	6.35	6.35	6.35
In-Plane Flow Rate <sup>4</sup>	ASTM D4716	gpm/ft	12	12	12	12	12	12
		Lpm/m	149	149	149	149	149	149
<b>COMPOSITE</b>								
Roll Size	MEASURED	ft	4 x 50	4 x 50	4 x 50	4 x 50	4 x 50	4 x 50

<sup>1</sup> Unless otherwise noted, all physical and performance properties listed are Typical Value as defined in ASTM D4439.

<sup>2</sup> PP = Polypropylene; NPNW = Needle-Punched Nonwoven; WM = Woven Monofilament; SBNW = Spunbonded Nonwoven

<sup>3</sup> Values for AOS represent Maximum Average Roll Value (MaxARV).

<sup>4</sup> In-plane flow rate measured at 3,600 psf (172 kPa) compressive load and a hydraulic gradient of 1.0.


All technical information contained in this document is accurate as of publication. AWD reserves the right to make changes to products and literature without notice. Please refer to our website for the most current technical information available.

# SITEDRAIN™ SHEET 110 SERIES

## PREFABRICATED SHEET DRAIN



### PRODUCT OVERVIEW



SITEDRAIN Sheet 110 Series geocomposite sheet drain products are composed of a dimpled polymeric core with a geotextile bonded to the dimple side. The geotextile allows water to pass through while retaining backfill materials. The solid core allows water collection from one side and provides a continuous flow path to designated drainage exits.

SITEDRAIN Sheet 110 Series products provide an economical solution for single-sided subsurface drainage applications requiring moderate strength and high flow capacity. Various geotextile options are available to meet project-specific requirements.

PROPERTY <sup>1</sup>	TEST METHOD	UNIT OF MEASURE	113	114	114-T	116	116-W	118
<b>GEOTEXTILE</b>								
Material <sup>2</sup>			PP, NPNW	PP, NPNW	PP, SBNW	PP, NPNW	PP, WM	PP, NPNW
Survivability	AASHTO M288	Class	-	3	3	2	-	1
Grab Tensile Strength	ASTM D4632	lbs	100	135	150	195	430 x 240	245
		N	445	601	667	867	1,914 x 1,068	1,090
Grab Elongation	ASTM D4632	%	70	60	50	60	30 x 15	60
CBR Puncture	ASTM D6241	lbs	305	365	295	505	800	580
		N	1,356	1,624	1,312	2,246	3,560	2,580
Trapezoidal Tear	ASTM D4533	lbs	50	60	70	85	180 x 130	100
		N	222	267	310	378	801 x 579	445
UV Resistance	ASTM D4355	% / 500 Hrs	70	70	70	70	90	70
Apparent Opening Size (AOS) <sup>3</sup>	ASTM D4751	sieve	70	70	80	70	50	80
		mm	0.212	0.212	0.180	0.212	0.300	0.180
Permittivity	ASTM D4491	sec <sup>-1</sup>	2.7	2.4	1.0	2.1	2.7	1.8
Water Flow Rate	ASTM D4491	gpm / ft <sup>2</sup>	165	175	70	155	195	135
		Lpm / m <sup>2</sup>	6,724	7,130	2,850	6,315	7,944	5,501
<b>CORE</b>								
Compressive Strength	ASTM D6364	psf	11,000	11,000	11,000	11,000	11,000	11,000
	ASTM D1621	kPa	527	527	527	527	527	527
Thickness	ASTM D5199	in	0.4	0.4	0.4	0.4	0.4	0.4
		mm	10	10	10	10	10	10
In-Plane Flow Rate <sup>4</sup>	ASTM D4716	gpm/ft	18	18	18	18	18	18
		Lpm/m	224	224	224	224	224	224
<b>COMPOSITE</b>								
Roll Size	MEASURED	ft	4 x 50	4 x 50	4 x 50	4 x 50	4 x 50	4 x 50
			-	6 x 50	6 x 50	6 x 50	6 x 50	6 x 50
			-	8 x 50	8 x 50	8 x 50	8 x 50	8 x 50

<sup>1</sup> Unless otherwise noted, all physical and performance properties listed are Typical Value as defined in ASTM D4439.

<sup>2</sup> PP = Polypropylene; NPNW = Needle-Punched Nonwoven; WM = Woven Monofilament; SBNW = Spunbonded Nonwoven

<sup>3</sup> Values for AOS represent Maximum Average Roll Value (MaxARV).

<sup>4</sup> In-plane flow rate measured at 3,600 psf (172 kPa) compressive load and a hydraulic gradient of 1.0.


All technical information contained in this document is accurate as of publication. AWD reserves the right to make changes to products and literature without notice. Please refer to our website for the most current technical information available.

# SITEDRAIN™ SHEET 180 SERIES

## PREFABRICATED SHEET DRAIN



### PRODUCT OVERVIEW



SITEDRAIN Sheet 180 Series geocomposite sheet drain products are composed of a dimpled polymeric core with a geotextile bonded to the dimple side. The geotextile allows water to pass through while retaining backfill materials. The solid core allows water collection from one side and provides a continuous flow path to designated drainage exits.

SITEDRAIN Sheet 180 Series products provide an economical solution for single-sided subsurface drainage applications requiring high strength and high flow capacity. Various geotextile options are available to meet project-specific requirements.

PROPERTY <sup>1</sup>	TEST METHOD	UNIT OF MEASURE	183	184	184-T	186	186-W	188
<b>GEOTEXTILE</b>								
Material <sup>2</sup>			PP, NPNW	PP, NPNW	PP, SBNW	PP, NPNW	PP, WM	PP, NPNW
Survivability	AASHTO M288	Class	-	3	3	2	-	1
Grab Tensile Strength	ASTM D4632	lbs	100	135	150	195	430 x 240	245
		N	445	601	667	867	1,914 x 1,068	1,090
Grab Elongation	ASTM D4632	%	70	60	50	60	30 x 15	60
CBR Puncture	ASTM D6241	lbs	305	365	295	505	800	580
		N	1,356	1,624	1,312	2,246	3,560	2,580
Trapezoidal Tear	ASTM D4533	lbs	50	60	70	85	180 x 130	100
		N	222	267	310	378	801 x 579	445
UV Resistance	ASTM D4355	% / 500 Hrs	70	70	70	70	90	70
Apparent Opening Size (AOS) <sup>3</sup>	ASTM D4751	sieve	70	70	80	70	50	80
		mm	0.212	0.212	0.180	0.212	0.300	0.180
Permittivity	ASTM D4491	sec <sup>-1</sup>	2.7	2.4	1.0	2.1	2.7	1.8
Water Flow Rate	ASTM D4491	gpm / ft <sup>2</sup>	165	175	70	155	195	135
		Lpm / m <sup>2</sup>	6,724	7,130	2,850	6,315	7,944	5,501
<b>CORE</b>								
Compressive Strength	ASTM D6364	psf	18,000	18,000	18,000	18,000	18,000	18,000
	ASTM D1621	kPa	862	862	862	862	862	862
Thickness	ASTM D5199	in	0.4	0.4	0.4	0.4	0.4	0.4
		mm	10	10	10	10	10	10
In-Plane Flow Rate <sup>4</sup>	ASTM D4716	gpm/ft	21	21	21	21	21	21
		Lpm/m	261	261	261	261	261	261
<b>COMPOSITE</b>								
Roll Size	MEASURED	ft	4 x 50	4 x 50	4 x 50	4 x 50	4 x 50	4 x 50
			-	6 x 50	6 x 50	6 x 50	6 x 50	6 x 50
			-	8 x 50	8 x 50	8 x 50	8 x 50	8 x 50

<sup>1</sup> Unless otherwise noted, all physical and performance properties listed are Typical Value as defined in ASTM D4439.

<sup>2</sup> PP = Polypropylene; NPNW = Needle-Punched Nonwoven; WM = Woven Monofilament; SBNW = Spunbonded Nonwoven

<sup>3</sup> Values for AOS represent Maximum Average Roll Value (MaxARV).

<sup>4</sup> In-plane flow rate measured at 3,600 psf (172 kPa) compressive load and a hydraulic gradient of 1.0.

All technical information contained in this document is accurate as of publication. AWD reserves the right to make changes to products and literature without notice. Please refer to our website for the most current technical information available.

# AWD PRODUCT REPLACEMENT CHART <sup>1</sup>

## FOR CARLISLE (CCW) GEOCOMPOSITE DRAINAGE PRODUCTS

CARLISLE (CCW)	AWD MEETS / EXCEEDS <sup>2</sup>	AWD ALTERNATE <sup>3</sup>
MIRADRAIN 2000	SITEDRAIN SHEET 113	-
MIRADRAIN 2000DT	SITEDRAIN SHEET 116	-
MIRADRAIN 6000	SITEDRAIN SHEET 183	-
MIRADRAIN 6000DT	SITEDRAIN SHEET 186	-
MIRADRAIN 6000XL	SITEDRAIN SHEET 186	-
MIRADRAIN 6200	SITEDRAIN SHEET 183-B	-
MIRADRAIN 6200XL	SITEDRAIN SHEET 186-B	-
MIRADRAIN 8000-P	SITEDRAIN SHEET 216-W	SITEDRAIN SHEET 186-W
MIRADRAIN 9000	SITEDRAIN SHEET 186-W	-
MIRADRAIN 9800	SITEDRAIN SHEET 188	-
MIRADRAIN 9900	SITEDRAIN SHEET 336-W	SITEDRAIN SHEET 306-W
MIRADRAIN GR9400	-	AMERGREEN 100
MIRADRAIN HC	SITEDRAIN STRIP 9400 SERIES	SITEDRAIN HQ 244

<sup>1</sup> AWD manufactures a complete line of prefabricated drainage products for a wide range of construction applications. Critical design considerations typically include core compressive strength, water flow rate, and geotextile filter fabric strength and filtration properties. References to competitive products are intended as a guideline for selecting product equivalents or alternates and are offered for the user's investigation and verification. Product selection and determination of suitability is the sole responsibility of the user. Please contact AWD Technical Services for additional assistance regarding product selection for specific applications and project conditions.

<sup>2</sup> Recommended alternate when the competitive product is already specified on a project and the AWD alternate must "meet or exceed".

<sup>3</sup> Recommended alternate based on meeting the intended function/purpose of the competitive product in common applications.

# SITEDRAIN™

## VERTICAL INSTALLATION GUIDE

awd-usa.com | 800.242.WICK (9425)

AWD SITEDRAIN prefabricated geocomposite drainage products are engineered, subsurface drainage products that are durable, economical solutions for most drainage problems. AWD's long history of successful installations and extensive distributor relationships ensure that there is a SITEDRAIN product for your application.

This SITEDRAIN Vertical Installation Guide is designed to provide a brief product overview and all of the information necessary to choose and install a SITEDRAIN geocomposite drainage solution for your application. AWD is also standing by to answer your questions or provide assistance.



# GENERAL INFORMATION

SITDRAIN prefabricated geocomposite drainage products combine a thermoformed polymer core with geotextile fabrics laminated to one or both sides. The geotextile fabric promotes the formation of a natural soil filter while allowing water to enter the drainage core and be efficiently conveyed to an outlet or collection point. This reduces subsurface hydrostatic pressure adjacent to the protected structure.

AWD manufactures SITEDRAIN Sheet Drains, DS (Double-Sided) Sheet Drains, Chimney Drains and Combination Drains. The following information provides guidelines applicable to prefabricated drains in typical applications.



SITEDRAIN PRODUCT OVERVIEW	
Sheet Series	Large surface area, single-sided drainage. Flow capacity equivalent to 6 - 12 feet of drainage aggregate.
DS Sheet Series	Large surface area, double-sided drainage. Flow capacity equivalent to 6 - 12 feet of drainage aggregate.
Chimney Series	Special width single- or double-sided sheet drains to provide discrete drain coverage.
HQS Series	High flow capacity, double sided water collection system for sheet drains. Replacement for perforated pipe.
HQ Series	High flow capacity, single-sided water collection system for sheet drains. Replacement for perforated pipe.

## PACKAGING & SHIPPING:

AWD offers the following packaging and shipping options for SITEDRAIN products.

- Rolls loose packed (request only, additional lead time)
- Rolls loose in UVI bags (request only, additional cost)

## DELIVERY:

Materials shall be delivered in original, unopened, undamaged packaging bearing manufacturer's name and product identification.

- Care must be taken during unloading process to insure materials are not damaged.
- Materials shall remain in original packaging until time of installation.

## STORAGE:

SITEDRAIN products should be stored in a covered location protected from temperature extremes and direct sunlight.

- SITEDRAIN products shipped in UVI bags may be stored in an exposed environment for a cumulative maximum of 180 days.

## ENVIRONMENTAL CONSIDERATIONS:

- Limit unpackaged material UV exposure to a cumulative maximum of 14 days during installation.
- Do not install materials during high wind events.
- Do not expose materials to chemicals that are strong acids, strong bases, or high in solvents content.
- Protect materials from site construction damage, direct flames, and other environmental conditions that may damage the materials.

## TEMPERATURE GUIDELINES:

### INSTALLATION TEMPERATURE RESTRICTIONS:

AWD does not recommend installation when the ambient temperature is below 20°F or above 100°F.

### OPERATIONAL TEMPERATURE RESTRICTIONS:

AWD products should not be installed in applications where the long term operational temperature is expected to be below 20°F or above 150°F.

## HOT APPLIED LAYER RESTRICTIONS:

AWD does not recommend hot applied layers (i.e. asphalt, hot mix setting beds, etc.) with application temperatures greater than 200°F be applied directly in contact with drainage products. In instances where the application temperature is above 200°F, please contact AWD for technical assistance.

# INSTALLATION DETAILS

This document is provided as a guideline to address typical installation applications and conditions. Where noted, "AWD-XXX" refers to detail drawing numbers located in the Appendix of this installation guide that contain additional information. Contact your local AWD SITEDRAIN representative for project or application specific guidelines.

## ACCESSORIES:

AWD offers a complete line of Fittings & Accessories to facilitate the proper installation of our drainage products.

AWD Fitting & Joint Tape (AWD Tape) is recommended for the sealing, seaming, terminating and connecting details referenced in this document. Any tape designed for underground use is acceptable provided it offers a strong bond that will not deteriorate over time in typical or anticipated subsurface conditions.

## ATTACHMENT METHODS:

Common attachment methods for drainage products include construction adhesives, mechanical fasteners (typically using nail gun), double-sided tapes, insulation anchors, and nails through washers or wood lathing. Construction adhesives with high solvent contents should be avoided as they may damage prefabricated drainage products. Acceptable attachment methods are dependent on the underlying substrate and should be approved by the design engineer or architect. Suggested attachment options for common substrates may include the following:

**CONCRETE OR WOOD:** Construction adhesives, double-sided tape, or mechanical fasteners.



**SOIL:** 4-inch to 8-inch long galvanized nails on approximately 4-foot spacing. Nail length will vary depending upon the surface to which the prefabricated drain is being attached. Nails should have flat heads, and washers or wood lathing may be used to prevent the nail head from being driven through the prefabricated drain.

**WATERPROOFING MEMBRANES:** Construction adhesives, double-sided tape, or insulation anchors. Check with the waterproofing manufacturer for compatibility before using construction adhesives in conjunction with waterproofing materials.

## DRAINAGE CONNECTION FLANGE:

SITEDRAIN prefabricated sheet & combination drains are manufactured with a core flange on each roll. The flange is a flat section of plastic that extends beyond the molded dimples on one side. The flange is designed to connect rolls to each other to facilitate water flow and installation. Rolls are designed with integrated geotextile fabric flaps that extend beyond the flange edge to secure seams and terminate edges.

Rolls can be installed vertically (in columns) or horizontally (in rows) against the installation surface. All rolls should be installed with flanges oriented in a consistent manner.




### CONNECTING ROLLS:

1. Attach the first roll of sheet drain to the wall using recommended attachment method.
2. Attach additional rolls by placing the flush edge of the roll over the connection flange on the adjacent roll.
3. Use fabric flaps to secure seams.
4. Seal all edges of drain prior to backfill.

When rolls are installed horizontally (rows), the core flange should be at the top edge. Additional rolls should be installed the same way with the bottom, non-flange edge overlapping or "shingled" over the lower horizontal row flange. Integrated geotextile fabric flaps are used to cover seams by overlapping or "shingling" downward (see Detail AWD 200 below).

AWD Tape or approved spray adhesives can be used to secure geotextile fabric flaps in place prior to placement of backfill.



AWD-200

## SEALING EDGE TERMINATIONS & PENETRATIONS:

SITEDRAIN products are installed in subsurface applications and care should be taken when backfilling to ensure soil is not able to enter the prefabricated drainage core through roll seams or edges.

### SEAMS AND EDGES:

Fabric flaps are provided on AWD prefabricated drainage products to facilitate seam and edge terminations.


- SITEDRAIN single-sided Chimney Drain products provide geotextile fabric flaps on the long edges of each roll.
- SITEDRAIN double-sided Chimney Drain products are fully wrapped and sealed with no geotextile fabric flaps required..
- SITEDRAIN HQ/HQS Series products provide fabric flaps on the top/flange open edge to facilitate the connection of Sheet or DS Sheet products.

For additional security, spray approved adhesive or AWD Tape can be used to secure fabric flaps in place prior to backfill.

### NOTE:


The ends of all rolls/products without fabric flaps must be secured with tape or fabric prior to backfill. Detail Reference for Seams and Terminations - AWD-200, 201, 203, 205, 206, 207, 208.

## TERMINATION - Flange Edge - Vertical



AWD-201

## TERMINATION - Non-Flange Edge - Vertical



AWD-203

### PENETRATIONS:

Penetrations (such as pipes) through prefabricated drains should be sealed using AWD Tape to insure backfill material is not able to enter the drainage core.

### FABRIC CUTS:

Cuts in the fabric less than 2 inches wide should be sealed using AWD Tape. Cuts in the fabric larger than 2 inches wide require a patch of filter fabric (of the same type used on the drainage product) extending a minimum 3 inches in all directions beyond the damaged fabric be used to cover the cut. The patch should be secured in place over the cut using AWD Tape or approved spray adhesive.

### BACKFILLING:

The soil backfill type, lift depth and required compaction must be as specified in the project plans and/or specifications or as designated by the design engineer. Compactor exhaust must be directed away from the AWD Sitedrain product to prevent damages and care should be taken when working directly adjacent to AWD Sitedrain products with mechanical equipment. Backfill should be placed to 3" above Sitedrain drainage products to prevent direct sun exposure. Final backfill elevations will be as directed by the project plans and/or specifications.

# VERTICAL APPLICATIONS

## SITEDRAIN Sheet Drains


The area where Sitedrain geocomposite drainage products will be installed on a vertical structure should be clear and accessible with a suitably flat substrate prepared for the attachment of Sitedrain products. Refer to General Information and Installation Details sections for more complete installation guidelines.

### BACKFILLED WALL:

Install sheet drain with fabric side toward soil.

AWD Detail Reference for Backfilled Walls

- AWD-101 - Retaining Wall Drainage - French Drain
- AWD-102 - Retaining Wall Drainage - Weep Hole
- AWD-105 - Bridge Abutment - Combination Drain
- AWD-106 - Bridge Abutment - French Drain
- AWD-107 - Bridge Abutment - Weep Hole




### SHORING WALL:

Install sheet drain with fabric side toward shoring. Concrete or gunnite/shotcrete may be placed against the core side of the drain. Refer to "Discharge Details" section for weep hole connection instructions.


AWD Detail Reference for Shoring Walls

AWD-112 - Shoring Wall - Weep Hole



# SOIL NAIL WALL (CHIMNEY DRAINS):

Chimney Drains are special width sheet drains fully wrapped in filter fabric. The perforated core allows water entry from both sides. Place dimple side toward soil/shoring. Chimney drains are typically installed at spaced intervals in vertical wall or slope applications to relieve hydrostatic pressure and enhance installation ease for applications where full wall coverage is not practical or required.




# CUT-OFF DRAIN:

Install drain using soil nails with washers.

AWD Detail Reference for Cut-Off Drainage

AWD-133 - Cut-Off Drainage - Strip Drain

AWD-131 - Cut-Off Drainage - French Drain



AWD-130



FOR CUT-OFF DRAIN > 3.5' DEEP

# CUT-SLOPE DRAIN:

Install drain using soil nails with washers.

AWD Detail Reference for Cut-Slope Drainage

AWD-121 - Cut-Slope Drainage - French Drain



FOR TRENCH DRAINS > 3.5' DEEP

# TRENCH DRAIN:

Install drain using soil nails with washers.

AWD Detail Reference for Cut-Slope Drainage


AWD-138 - Trench Drainage - Strip Drain

AWD-136 - Trench Drainage - French Drain

# MSE WALL BACK DRAINAGE:

AWD Detail Reference for MSE Wall

AWD-136 - MSE Wall - French Drain




AWD-125

# SITEDRAIN HQ Perimeter Drain System

## INSTALLING SITEDRAIN HQ

When using SITEDRAIN HQ as the collection and conveyance system, install first roll of SITEDRAIN HQ at the bottom of the wall. The drain should sit on top of the footing (if applicable) with high-profile part of the drain at the bottom to provide high lateral water flow. Install sheet drain over the HQ core flange.


Refer to "General Information" and "Installation Details" sections for installation guidelines.




## CONNECTING HQ ROLLS

To attach the next roll of SITEDRAIN HQ drain, peel back fabric of SITEDRAIN HQ to expose one row of both low-profile and high-profile dimples on each connecting end. Cut and discard one row of low-profile dimples (do not cut high-profile dimples) from each connecting end. Do not cut fabric.

Interlock one row of the high-profile section and secure connection with AWD Tape.




SIDE VIEW -  
Interlock HQ Core





Overlap fabric flaps and tape to secure.

# HQ CORNER DETAILS


## Inside Corners



## Outside Corners



Bend drain around Inside Corner.  
Low and High Profile Sections



Low Profile: Terminate and Tape

High-Profile: Slit fabric and place AWD 12" Corner Guard Fitting over slit. Tape to secure.

# SITEDRAIN HQS Perimeter Drain System


## INSTALLING SITEDRAIN HQS

When using SITEDRAIN HQS as the collection and conveyance system, install first roll of SITEDRAIN HQS at the bottom of the wall or trench.

Install sheet drain over the HQS core flange.

NOTE: HQS has fabric flaps that extend beyond the flange on both the front and back side. Both fabric flaps must be secured prior to backfill.


Refer to "General Information" and "Installation Details" sections for installation guidelines.




## CONNECTING HQS ROLLS

To attach the next roll of SITEDRAIN HQS drain, peel back fabric of SITEDRAIN HQS to expose dimples on each connecting end.

Interlock one row of dimples, overlap fabric flaps on front and back sides. Secure connection with AWD Tape.



SIDE VIEW -  
Interlock HQS Core




# DISCHARGE OUTLET DETAILS


SITEDRAIN HQ drains are designed to connect directly to SITEDRAIN Sheet Drain products allowing collected water a fast, efficient, uninterrupted flow path to designated drainage outlets.

AWD Tee Outlet and End Outlet fittings are used to connect SITEDRAIN HQ to outlet pipes.

SITEDRAIN products can also be connected to weep hole outlets.



## Tee Outlet Connection:




Use razor knife to cut 3" wide x 4" high "V" notch through geocomposite drain fabric and core at desired Tee Outlet fitting location. Discard cut-out section.

PLACE "U" Channel of Tee Outlet fitting over "V" notch and secure bottom edge using AWD Tape.

Secure all fitting edges with AWD Tape.

Insert 4" pipe into Tee Outlet fitting and secure connection with AWD Tape. Double bell housing on fitting allows secure connection of 4" smooth or corrugated pipe.

## End Outlet Connection:



Place "U" Channel of End Outlet Fitting around bottom corner of geocomposite drain with fabric flap extending upwards.


Fold fabric around exposed edge of drain and secure with AWD Tape.

Secure all fitting edges with AWD Tape.

Insert 4" pipe into End Outlet fitting and secure connection with AWD Tape. Double bell housing on fitting allows secure connection of 4" smooth or corrugated pipe.

## Weep Connections:

AWD offers two options for weep connection discharge.



AWD-102



**Option 1 - Geo-Outlet**



**Option 2 - Drain Grate**


## Geo Outlet Connection:

Form a 4-inch diameter round hole in the prefabricated drain (through core and fabric) at the fitting connection location using the Geo Outlet Punch accessory or a standard utility knife.

Insert drainage collector through back of prefabricated drain.

Place All-Purpose Cement (compatible with both ABS and PVC plastic) on the portion of drainage collector that extends through prefabricated drain and attach retainer ring. Hand squeeze retainer ring to drainage collector to form a seal with prefabricated drain until cement sets (~10 seconds).

Place All-Purpose Cement on inside portion of drainage collector and attach 3-inch diameter SCH 40 PVC pipe. (not included).




AWD-324

## Additional References for Geo Outlets

- AWD-320 - Vertical Wall Tee Outlet
- AWD-322 - Backfilled Wall Tee Outlet
- AWD-321 - Vertical Wall Existing Weep Hole


## Drain Grate



Drill 1/4" holes into the flat plastic areas between dimples of the hard plastic core on the back (wall) side of the sheet drain at the weep hole location.

Do not drill through dimples or fabric.

Holes should extend in all directions to match the dimensions of the weep hole. The holes will allow water to flow from the sheet drain into the weep hole.




AWD-330

# ALTERNATE - FRENCH DRAIN

Terminate sheet drain at the footer.  
Allow sheet drain to discharge into drainage aggregate for transition to perforated pipe.  
Terminate bottom edge of drain with fabric or tape to prevent backfill material intrusion.

## Additional References - French Drain

- AWD-106 - Bridge Abutment - French Drain
- AWD-121 - Cut-Slope Drainage - French Drain
- AWD-131 - Cut-Off Drainage - French Drain
- AWD-136 - Trench Drainage - French Drain



## PRODUCT WARRANTY:

American Wick Drain Corporation ("AWD") warrants that the products shall be free from defects and in conformity, within normal manufacturing variations, with AWD's physical specifications. No other portion of AWD's published literature shall be incorporated herein except for such physical specifications. AWD shall be responsible for such defects only if the same is noted, in writing, within one (1) year from delivery of the products.

OTHER THAN THE WARRANTY IMMEDIATELY ABOVE, ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. THE REMEDIES PROVIDED HEREUNDER SHALL BE EXCLUSIVE; AWD SHALL NOT BE LIABLE FOR ANY PERSONAL INJURY, OTHER DIRECT, INDIRECT, CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES OF ANY KIND (INCLUDING COST OF INSTALLATION, REMOVAL OR REPAIR OF THE PRODUCT OR LOSS OF USE OR PROFIT).

1209 Airport Rd, Monroe, NC 28110  
TF: 800.242.9425 PH: 704.238.9200  
info@awd-usa.com

[www.awd-usa.com](http://www.awd-usa.com)

