



## TECHNICAL DATA SHEET

# XY Xylene Solvent

## Specialty Clean™



### NOTICE

Make sure you have an up-to-date technical data sheet by referencing our website: [SRWProducts.com](http://SRWProducts.com)

### DESCRIPTION

Specialty Clean™ XY Xylene Solvent is a fast-acting solvent that thins and dissolves acrylic sealers to aid in tool clean-up and overspray. Before using XY to thin or reduce any coating, check the coatings data sheet for guidance and compliance with the Federal Clean Air Act of 1990.

### APPLICATIONS

- Aids in clean-up of tools
- Removes unwanted overspray
- Thins and dissolves acrylic sealers
- Removes trapped moisture in most film-forming sealers

### PROPERTIES

- Fast-acting solvent

### COVERAGE

- Up to 200 sq. ft. per gallon (18.58 sq. m. per 3.78 liters).
- Coverage may vary depending on surface and application.

### INSTALLATION INSTRUCTIONS TO CLEAN SPRAYERS

1. Flush sprayers (metal canister type with Viton seals) with XY.
2. Leave approximately one pint of solvent in the sprayer when not in use to ensure against clogging the hose and tip. **NOTE:** For routine use, place nozzle in solvent can, pump sprayer to force solvent up into the hose, handle and wand area, spray until steady stream of solvent occurs, and let stand overnight.

### FOR SEALER OVERSPRAY/HEAVY COAT

1. Test a small, discrete area before applying XY.
2. Saturate a cotton cloth and rub the affected area.

### FOR BLUSHING

1. Test a small, discrete area before applying XY.
2. Apply XY to the affected areas and use an SRW Slit Foam Roller to distribute.

**SRW Products**  
800-752-9326

32005 126th St.  
PO Box 70  
Princeton, MN 55371

[SRWProducts.com](http://SRWProducts.com)

Revised: 03-22-2021

Specialty Clean™ XY Xylene Solvent Technical Data Sheet

Page 1 of 2

## STORAGE AND SHELF LIFE

Store container in a cool area with cap or lid firmly in place. Keep container closed when not in use. If spilled, eliminate all sources of ignition. Contain spilled material and remove with inert absorbent using non-sparking tool. Dispose of contaminated absorbent, container, and unused contents in accordance with all applicable regulations.

## WARNINGS

**CONTAINS PETROLEUM DISTILLATES. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE, AND THROAT IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL IF SWALLOWED. DO NOT TAKE INTERNALLY.**

**WARNING:** Keep away from heat, sparks, and flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe vapors or spray mists. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If swallowed, DO NOT INDUCE VOMITING. Give conscious victim 1–2 glasses of water and get medical attention immediately.

**IN CASE OF FIRE:** Use CO2 or dry chemical extinguisher. Do not use water spray.

**IMPORTANT NOTICE:** Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only. For information and installation instructions visit, [SRWproducts.com](http://SRWproducts.com).

**SHIPPING:** DOT Shipping name: Not regulated  
VOC 868 g/L (7.25 lbs/gallon)

## PACKAGING

Specialty Clean™ XY Xylene Solvent			
PART #	SIZE	AMT PER CTN	QUANTITY
SSS XY CTN	1 gal	4/CTN	36 CTNS/PLT
SSS XY	5 gal	1	36/PLT

SRW Products  
800-752-9326

32005 126th St.  
PO Box 70  
Princeton, MN 55371

[SRWProducts.com](http://SRWProducts.com)

Revised: 03-22-2021

Specialty Clean™ XY Xylene Solvent Technical Data Sheet

Page 2 of 2